ISO 5136:2003-04 (E)

Acoustics - Determination of sound power radiated into a duct by fans and other air-moving devices - In-duct method

Contents

Page

Foreword iv

Introduction v

1 Scope 1
1.1 General 1
1.2 Types of sound source 1

2 Normative references 2

3 Terms, definitions and symbols 2

4 Uncertainty of the measurement method 7

5 Test facilities and instrumentation 8
5.1 General requirements 8
5.2 Duct specifications 9
5.3 Instrumentation 16
5.4 System calibration 19

6 Test arrangement 20
6.1 Sampling tube mounting 20
6.2 Microphone position 20
6.3 Operating condition control equipment 21

7 Test procedure 21
7.1 Operating conditions 21
7.2 Sound pressure level readings 21
7.3 Measurements with and without flow straightener on the outlet side 22
7.4 Inlet side measurements -- Large fans: installation category D (according to ISO 5801:1997) 22

8 Calculations 23
8.1 Average sound pressure level 23
8.2 Sound power level 23

9 Information to be recorded 24

10 Information to be reported 24

Annex A (normative) Determination of the combined mean flow velocity and modal correction C3,4 25

Annex B (normative) Determination of the signal-to-noise ratio of sound vs. turbulent pressure fluctuation in the test duct 31

Annex C (normative) Computational procedures for calculating the A-weighted sound power level from one-third-octave-band sound power levels 34

Annex D (informative) Example of calculation of C3,4 for a given duct diameter and mean flow velocity 35

Annex E (informative) Guidelines for the design and construction of an anechoic termination 38

Annex F (informative) Evaluation of performance of anechoic terminations 47

Annex G (informative) Sampling tube information 50

Annex H (informative) Test method for small ducted fans 54

Annex I (informative) Test method for large ducted fans 58

Annex J (informative) Measurement of the swirl component 65

Bibliography 66