

ISO 5136:2003-04 (E)

Acoustics - Determination of sound power radiated into a duct by fans and other air-moving devices - In-duct method

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
1.1	General	1
1.2	Types of sound source	1
2	Normative references	2
3	Terms, definitions and symbols	2
4	Uncertainty of the measurement method	7
5	Test facilities and instrumentation	8
5.1	General requirements	8
5.2	Duct specifications	9
5.3	Instrumentation	16
5.4	System calibration	19
6	Test arrangement	20
6.1	Sampling tube mounting	20
6.2	Microphone position	20
6.3	Operating condition control equipment	21
7	Test procedure	21
7.1	Operating conditions	21
7.2	Sound pressure level readings	21
7.3	Measurements with and without flow straightener on the outlet side	22
7.4	Inlet side measurements -- Large fans: installation category D (according to ISO 5801:1997)	22
8	Calculations	23
8.1	Average sound pressure level	23
8.2	Sound power level	23
9	Information to be recorded	24
10	Information to be reported	24
Annex A (normative)	Determination of the combined mean flow velocity and modal correction C_{3,4}	25
Annex B (normative)	Determination of the signal-to-noise ratio of sound vs. turbulent pressure fluctuation in the test duct	31
Annex C (normative)	Computational procedures for calculating the A-weighted sound power level from one-third-octave-band sound power levels	34
Annex D (informative)	Example of calculation of C_{3,4} for a given duct diameter and mean flow velocity	35

Annex E (informative) Guidelines for the design and construction of an anechoic termination	38
Annex F (informative) Evaluation of performance of anechoic terminations	47
Annex G (informative) Sampling tube information	50
Annex H (informative) Test method for small ducted fans	54
Annex I (informative) Test method for large ducted fans	58
Annex J (informative) Measurement of the swirl component	65
Bibliography	66