# ISO 15712-1:2005-01 (E)

## Building acoustics - Estimation of acoustic performance of buildings from the performance of elements - Part 1: Airborne sound ins ulation between rooms

## Contents

Page


Foreword ..... v

1 Scope ..... 1

2 Normative references ..... 1

3 Relevant quantities ..... 2
3.1 Quantities to express building performance ..... 2
3.1.1 Apparent sound reduction index R' ..... 2
3.1.2 Standardized level difference DnT ..... 2
3.1.3 Normalized level difference Dn ..... 3
3.1.4 Relation between quantities ..... 3
3.2 Quantities to express element performance ..... 3
3.2.1 Sound reduction index R ..... 3
3.2.2 Sound reduction index improvement R ..... 3
3.2.3 Element normalized level difference Dn,e ..... 4
3.2.4 Normalized level difference for indirect airborne transmission Dn,s ..... 4
3.2.5 Flanking normalized level difference Dn,f ..... 4
3.2.6 Vibration reduction index Kij ..... 5
3.2.7 Other element data ..... 5
3.3 Other terms and quantities ..... 6
3.3.1 Direct transmission ..... 6
3.3.2 Indirect transmission ..... 6
3.3.3 Indirect airborne transmission ..... 6
3.3.4 Indirect structure-borne transmission (flanking transmission) ..... 6
3.3.5 Direction-averaged junction velocity level difference ijv,D ..... 6
3.3.6 Flanking sound reduction index Rij ..... 6

4 Calculation models ..... 7
4.1 General principles ..... 7
4.2 Detailed model for structure-borne transmission ..... 9
4.2.1 Input data ..... 9
4.2.2 Transfer of input data to in-situ values ..... 10
4.2.3 Determination of direct and flanking transmission in-situ ..... 12
4.2.4 Interpretation for several types of elements ..... 13
4.2.5 Limitations ..... 16
4.3 Detailed model for airborne transmission ..... 16
4.3.1 Determination from measured direct transmission for small elements ..... 16
4.3.2 Determination from measured total indirect transmission ..... 17
4.3.3 Determination from measured transmission for the separate elements of a system ..... 17
4.4 Simplified model for structure-borne transmission ..... 17
4.4.1 Calculation procedure ..... 17
4.4.2 Input data ..... 19
4.4.3 Limitations ..... 20

5 Accuracy ..... 20

Annex A (normative) Symbols ..... 21

Annex B (informative) Sound reduction index for monolithic elements ..... 25

B.1 Sound reduction index in frequency bands ..... 25
B.2 Weighted sound reduction index ..... 28

Annex C (informative) Structural reverberation time ..... 31

Annex D (informative) Sound reduction index improvement of additional layers ..... 34

D.1 Sound reduction index improvement of layers ..... 34
D.1.1 Direct transmission, R ..... 34
D.1.2 Flanking transmission ..... 34
D.2 Weighted sound reduction index improvement of layers ..... 36

Annex E (informative) Vibration reduction index for junctions ..... 38

E.1 Determination methods ..... 38
E.2 Empirical data ..... 38
E.3 Limiting values ..... 39

Annex F (informative) Determination of indirect transmission ..... 47

F.1 Laboratory measurement of total indirect transmission ..... 47
F.1.1 Indirect airborne transmission ..... 48
F.1.2 Flanking transmission ..... 49
F.2 Determination of indirect airborne transmission from known transmission for the separate elements of a system ..... 49
F.2.1 Hall or corridor ..... 49
F.2.2 Ventilation system ..... 50

Annex G (informative) Laboratory weighted sound reduction index including field simulated flanking transmission ('Prüfstand mit bauähnlicher Flankenübertragung', DIN 52210) ..... 51

Annex H (informative) Calculation examples ..... 53

H.1 Situation ..... 53
H.2 Detailed model ..... 54
H.2.1 Results ..... 54
H.2.2 Detailed steps for separating element, floor and inner wall ..... 54
H.2.3 Structural reverberation time partition wall at 500 Hz octave : ..... 56
H.3 Simplified model ..... 57

Bibliography ..... 59