

# ISO 18437-3:2005-04 (E)

## Mechanical vibration and shock - Characterization of the dynamic mechanical properties of visco-elastic materials - Part 3: Cantilever shear beam method

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>2</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Test equipment (see Figure 1) .....</b>	<b>3</b>
<b>4.1</b>	<b>Electro-dynamic vibration generator .....</b>	<b>3</b>
<b>4.2</b>	<b>Force measurement .....</b>	<b>3</b>
<b>4.3</b>	<b>Displacement transducer .....</b>	<b>4</b>
<b>4.4</b>	<b>Clamping system .....</b>	<b>4</b>
<b>4.5</b>	<b>Environmental chamber .....</b>	<b>5</b>
<b>4.6</b>	<b>Computer .....</b>	<b>5</b>
<b>5</b>	<b>Operating procedure .....</b>	<b>5</b>
<b>5.1</b>	<b>Sample preparation and mounting .....</b>	<b>5</b>
<b>5.2</b>	<b>Conditioning .....</b>	<b>6</b>
<b>5.3</b>	<b>Cantilever shear beam analysis .....</b>	<b>7</b>
<b>5.4</b>	<b>Calibration and measurement .....</b>	<b>8</b>
<b>5.5</b>	<b>Number of test pieces .....</b>	<b>8</b>
<b>5.6</b>	<b>Temperature cycle .....</b>	<b>8</b>
<b>6</b>	<b>Analysis of results .....</b>	<b>9</b>
<b>6.1</b>	<b>Time-temperature superposition .....</b>	<b>9</b>
<b>6.2</b>	<b>Data presentation .....</b>	<b>9</b>
<b>6.3</b>	<b>Test report .....</b>	<b>10</b>
<b>Annex A (informative) Linearity of resilient materials .....</b>		<b>11</b>
<b>Annex B (informative) Time-temperature superposition .....</b>		<b>12</b>
<b>Bibliography .....</b>		<b>14</b>