

ISO 16063-22:2005-06 (E)

Methods for the calibration of vibration and shock transducers - Part 22: Shock calibration by comparison to a reference transducer

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Uncertainty of measurement | 2 |
| 5 | Apparatus | 3 |
| 5.1 | General considerations | 3 |
| 5.2 | Anvil shock calibrators (100 m/s ² to 100 km/s ²) | 3 |
| 5.3 | Hopkinson bar shock calibrators | 8 |
| 5.4 | Oscilloscope | 9 |
| 5.5 | Waveform recorder with computer interface | 9 |
| 5.6 | Computer with data-processing capability | 10 |
| 5.7 | Filters | 10 |
| 5.8 | Other requirements | 10 |
| 6 | Ambient conditions | 10 |
| 7 | Preferred accelerations and pulse durations | 10 |
| 8 | Method | 11 |
| 8.1 | Test procedure | 11 |
| 8.2 | Data acquisition | 11 |
| 8.3 | Signal processing | 11 |
| 9 | Reporting the calibration results | 15 |
| Annex A (normative) Expression of uncertainty of measurement in calibration | | 16 |
| Annex B (informative) Uncertainty examples -- Expression of uncertainty of measurement in calibration | | 19 |
| Bibliography | | 22 |