

DIN EN ISO 10848-1:2006-08 (E)

Acoustics - Laboratory measurement of the flanking transmission of airborne and impact sound between adjoining rooms - Part 1: Frame document (ISO 10848-1:2006)

Contents		Page
Foreword		2
1	Scope	4
2	Normative references	4
3	Terms and definitions	5
4	Quantities to characterize flanking transmission	9
4.1	General	9
4.2	Normalized flanking level difference $D_{n,f}$ and normalized flanking impact sound pressure level $L_{n,f}$	9
4.3	Vibration reduction index, K_{ij}	9
4.4	Selection of the principle of measurement	11
5	Measuring equipment	12
6	General requirements for test specimens and test rooms	12
7	Measurement methods	13
7.1	Measurement of $D_{n,f}$ and $L_{n,f}$	13
7.2	Measurement of the vibration reduction index with structure-borne excitation	15
7.3	Measurement of the structural reverberation time	18
7.4	Measurement of the vibration reduction index with airborne excitation	19
7.5	Frequency range of measurement	20
8	Influences from the structures of the test facility	20
8.1	Criterion to verify flanking transmissions through constructions of the test facility	20
8.2	Conventional limit for light elements compared with the surrounding elements of the test facility	21
8.3	Verification procedure for a light flanking element that is structurally independent of a separating element	21
9	Shielding	21
Annex A (normative) Single-number rating of the vibration reduction index		27
Bibliography		28