ISO 16063-15:2006-08 (E)

Methods for the calibration of vibration and shock transducers - Part 15: Primary angular vibration calibratio n by laser interferometry

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 2

3 Uncertainty of measurement 2

4 Requirements for apparatus 2
4.1 General 2
4.2 Frequency generator and indicator 3
4.3 Power amplifier/angular vibration exciter combination 3
4.4 Seismic block(s) for vibration exciter and laser interferometer 5
4.5 Laser 5
4.6 Interferometer 5
4.7 Instrumentation for interferometer signal processing 8
4.8 Voltage instrumentation, measuring true r.m.s. accelerometer output 9
4.9 Distortion-measuring instrumentation 9
4.10 Oscilloscope (optional) 9
4.11 Other requirements 9

5 Ambient conditions 9

6 Preferred angular accelerations and frequencies 10

7 Common procedure for all six methods 10

8 Methods using fringe-counting (methods 1A and 1B) 11
8.1 General 11
8.2 Common test procedure for methods 1A and 1B 12
8.3 Expression of results 12

9 Methods using minimum-point detection (methods 2A and 2B) 16
9.1 General 16
9.2 Common test procedure for methods 2A and 2B 17
9.3 Expression of results 17

10 Methods using sine approximation (methods 3A and 3B) 21
10.1 General 21
10.2 Procedure applied to methods 3A and 3B 22
10.3 Data acquisition 27
10.4 Data processing 27

11 Reporting of calibration results 29

Annex A (normative) Uncertainty components in primary angular vibration calibration of vibration and shock transducers by laser interferometry 30

Annex B (normative) Equations for the calculation of the angular quantities of rotational angle, , angular velocity, , and angular acceleration, , and of the sensitivities of angular transducers: rotational angle transducers, S, of angular velocity transducers, S, and angular accelerometers, S 36

Bibliography 42