

ISO/TS 4869-5:2006-10 (E)

Acoustics - Hearing protectors - Part 5: Method for estimation of noise reduction using fitting by inexperienced test subjects

Contents		Page
Foreword		v
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Measurement of the noise reduction of hearing protectors	3
4.1	Test signals	3
4.2	Test site	3
4.2.1	Conditions to be met for the test to be valid	3
4.2.2	Reverberation time	4
4.2.3	Background noise	4
4.3	Test equipment	5
5	Test subjects	6
5.1	Conditions for subject acceptance/dismissal	6
5.1.1	General	6
5.1.2	Age and sex	6
5.1.3	Previous experience with hearing protectors	7
5.1.4	Anatomical features	7
5.1.5	Maximum hearing threshold levels	7
5.1.6	Minimum hearing threshold levels	7
5.1.7	Literacy	7
5.1.8	Threshold variability	7
5.2	Number of subjects	7
5.3	Otoscopic inspection	8
5.4	Spectacles and jewellery	8
5.5	Maximum number of tests per subject	8
5.6	Exceptions	8
6	Product samples	8
6.1	General	8
6.2	Custom-moulded ear-plugs	8
6.3	Special requirements for product instruction	8
6.4	Variable position headbands	9
6.5	Variable band force	9
7	Test procedure	9
7.1	Number of open-ear and occluded-ear threshold measurements	9
7.2	Information to subjects	9
7.3	Prior to entering the test room	10
7.4	Inside the test room	10
7.4.1	Positioning the subject	10
7.4.2	Quiet period prior to first threshold determination	11
7.4.3	Fitting the hearing protector for test	11
7.4.4	Re-determination of thresholds	11

8	Computation of noise reduction values	12
8.1	General	12
8.2	Calculation of the individual noise reductions	12
8.3	Calculation of group noise reduction	12
8.4	Uncertainty of the noise reduction data	13
9	Reporting of data	13
	Annex A (informative) Uncertainty of hearing protector noise reduction measurements	15
	Bibliography	18