

DIN EN 16842-6:2019-06 (E)

Powered industrial trucks - Visibility - Test methods and verification - Part 6: Sit-on counterbalance trucks and rough terrain masted trucks greater than 10000 kg capacity

| Contents | | Page |
|--|---|-------------|
| European foreword | | 3 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Truck configuration | 6 |
| 4.1 | General | 6 |
| 4.2 | Height of load carrying surface | 6 |
| 4.3 | Fork arm dimensions | 7 |
| 5 | Test equipment | 7 |
| 6 | Test procedures for direct visibility | 7 |
| 6.1 | Lighting equipment position | 7 |
| 6.2 | Test paths for trucks > 10 000 kg | 8 |
| 6.3 | Measurement procedure | 10 |
| 6.4 | Test procedure for indirect visibility | 10 |
| 7 | Acceptance criteria | 10 |
| 7.1 | General | 10 |
| 7.2 | Direct visibility | 10 |
| 7.2.1 | General | 10 |
| 7.2.2 | Travelling visibility | 10 |
| 7.2.3 | Manoeuvring visibility | 10 |
| 7.2.4 | Fork arms | 10 |
| 7.3 | Indirect visibility | 10 |
| 7.4 | Criteria for trucks greater than 10 000 kg rated capacity | 11 |
| 8 | Test report | 12 |
| 9 | Information for use | 12 |
| Annex A (informative) Information for operator visibility during use | | 13 |
| A.1 | General | 13 |
| A.2 | Method 1 | 14 |
| A.3 | Method 2 | 15 |
| Bibliography | | 16 |