ISO 10303-111:2007-05 (E)

Industrial automation systems and integration - Product data representation and exchange - Part 111: Integrated application resource: Elements for the procedural modelling of solid shapes

Contents

Page

1 Scope 1

2 Normative references 2

3 Terms, definitions and abbreviations 2
3.7 Other terms and definitions 4
3.8 Abbreviations 4

4 Solid shape element 5
4.1 Introduction 5
4.2 Fundamental concepts and assumptions 6
4.3 Solid shape element type definitions 7
4.3.1 base solid select 7
4.3.2 blend end condition select 8
4.3.3 generalized surface select 8
4.3.4 trim condition select 9
4.3.5 blend radius variation type 9
4.3.6 trim intent 9
4.4 Solid shape element entity definitions 10
4.4.1 modified solid 10
4.4.2 edge blended solid 11
4.4.3 track blended solid 12
4.4.4 track blended solid with end conditions 13
4.4.5 solid with constant radius edge blend 15
4.4.6 solid with variable radius edge blend 17
4.4.7 solid with chamfered edges 20
4.4.8 solid with single offset chamfer 21
4.4.9 solid with double offset chamfer 21
4.4.10 solid with angle based chamfer 22
4.4.11 surfaced open shell 24
4.4.12 sculptured solid 25
4.4.13 sculptured solid with selection 26
4.4.14 offset face solid 27
4.4.15 shelled solid 28
4.4.16 double offset shelled solid 30
4.4.17 complex shelled solid 31
4.4.18 modified solid with placed configuration 31
4.4.19 solid with depression 32
4.4.20 solid with through depression 33
4.4.21 solid with hole 34
4.4.22 solid with stepped round hole 34
4.4.23 conical stepped hole transition 35
4.4.24 solid with stepped round hole and conical transitions 37
4.4.25 solid with flat bottom round hole 38
4.4.26 solid with spherical bottom round hole 39
4.4.27 solid with conical bottom round hole 40
4.4.28 solid with pocket 41
4.4.29 solid with rectangular pocket 42
4.4.30 solid with circular pocket 44

4.4.31 solid with general pocket ... 45
4.4.32 solid with slot ... 46
4.4.33 solid with straight slot ... 47
4.4.34 solid with curved slot ... 49
4.4.35 solid with trapezoidal section slot ... 49
4.4.36 solid with tee section slot ... 50
4.4.37 solid with groove ... 52
4.4.38 solid with protrusion ... 54
4.4.39 solid with circular protrusion ... 54
4.4.40 solid with rectangular protrusion ... 55
4.4.41 solid with general protrusion ... 56
4.4.42 solid with shape element pattern ... 56
4.4.43 solid with circular pattern ... 57
4.4.44 solid with rectangular pattern ... 59
4.4.45 solid with incomplete circular pattern ... 60
4.4.46 solid with incomplete rectangular pattern ... 61
4.4.47 thickened face solid ... 62
4.4.48 extruded face solid with trim conditions ... 64
4.4.49 extruded face solid with draft angle ... 67
4.4.50 extruded face solid with multiple draft angles ... 67
4.4.51 revolved face solid with trim conditions ... 68
4.4.52 auxiliary geometric instance aggregator ... 70
4.5 Solid shape element function definitions ... 71
4.5.1 check continuous edges ... 71
4.5.2 compute total depth ... 72
4.5.3 validate countersink radii ... 73

Annex A (normative) Short names of entities ... 75

Annex B (normative) Information object registration ... 77

B.1 Document identification ... 77
B.2 Schema identification ... 77

Annex C (informative) Computer interpretable listings ... 78

Annex D (informative) EXPRESS-G diagrams ... 79

E.1 Representation of constructional operations ... 91
E.2 Representation of local shape configurations ... 92

Bibliography ... 93

Index ... 94

Figures Figure 1 Schema level diagram of relationships between the solid - shape element schema
Figure 2 L-section block ... 16

Figure 3 L-section block of Figure 2 with constant radius edge blend ... 16

Figure 4 A track blended solid with a constant radius edge blend ... 17

Figure 5 L-section block of Figure 2 with variable radius edge blend ... 19

Figure 6 A track blended solid with end conditions for which the blend radius is variable ... 19

Figure 7 Solid with double offset chamfer ... 22

Figure 8 Solid with angle based chamfer ... 24

Figure 9 Solid and generalized surface defining a sculptured solid ... 26

Figure 10 The sculptured solid after the partitioning operation 26

Figure 11 Offset face solid 28

Figure 12 Shelled solid 30

Figure 13 Cross-section of solid with stepped round hole 36

Figure 14 Cross-section of solid with stepped round hole and conical transitions 38

Figure 15 Bottom conditions for blind round holes 41

Figure 16 Solid with rectangular pocket 44

Figure 17 Solid with straight slot, having two closed ends 48

Figure 18 Straight slot with multiple entries and exits from part material 48

Figure 19 Trapezoidal and T slot sections 51

Figure 20 Solid with groove 53

Figure 21 The effect of radial alignment in solid with circular pattern 58

Figure 22 Solid with rectangular pattern 60

Figure 23 Solid with incomplete circular pattern 61

Figure 24 Solid with incomplete rectangular pattern 62

Figure 25 Thickened face solid 63

Figure 26 Extruded face solid with draft angle 66

Figure D.1 solid shape element schema - EXPRESS-G diagram 1 of 11 80

Figure D.2 solid shape element schema - EXPRESS-G diagram 2 of 11 81

Figure D.3 solid shape element schema - EXPRESS-G diagram 3 of 11 82

Figure D.4 solid shape element schema - EXPRESS-G diagram 4 of 11 83

Figure D.5 solid shape element schema - EXPRESS-G diagram 5 of 11 84

Figure D.6 solid shape element schema - EXPRESS-G diagram 6 of 11 85

Figure D.7 solid shape element schema - EXPRESS-G diagram 7 of 11 86

Figure D.8 solid shape element schema - EXPRESS-G diagram 8 of 11 87

Figure D.9 solid shape element schema - EXPRESS-G diagram 9 of 11 88

Figure D.10 solid shape element schema - EXPRESS-G diagram 10 of 11 89

Figure D.11 solid shape element schema - EXPRESS-G diagram 11 of 11 90

Tables A.1 Short names of entities 75