DIN ISO 8132:2008-06 (E)

Hydraulic fluid power - Single rod cylinders, 16 MPa (160 bar) medium and 25 MPa (250 bar) series - Mounting dimens ions for accessories (ISO 8132:2006)

Contents

Page

National foreword 3

Introduction 4

1 Scope 5

2 Normative references 6

3 Terms and definitions 6

4 Mounting dimensions 6

5 Material -- Load capacity 6

6 Application instructions 6
6.1 Installation 6
6.2 Lubrication 6

7 Designation 7

8 Identification statement (Reference to this International Standard) 7

Figures Figure 1 -- AP2 -- Rod clevis, female thread 8

Figure 2 -- AF3 -- Rod flange, circular 9

Figure 3 -- AB4 -- Clevis bracket, straight 10

Figure 4 -- AB3 -- Clevis bracket, in angle 11

Figure 5 -- AT4 - Trunnion bracket 12

Figure 6 -- AA8 -- Pivot pin, plain or spherical bearing (cotter pin or snap ring type) 13

Figure 7 -- AP6 -- Rod eye spherical, female thread 14

Figure 8 -- AP4 -- Rod eye plain, female thread 15

Tables Table 1 -- Dimensions of AP2 -- Rod clevis, female thread 8

Table 2 -- Dimensions of AF3 -- Rod flange, circular 9

Table 3 -- Dimensions of AB4 -- Clevis bracket, straight 10

Table 4 -- Dimensions of AB3 -- Clevis bracket, in angle 11

Table 5 -- Dimensions of AT4 - Trunnion bracket 12

Table 6 -- Dimensions of AA8 -- Pivot pin, plain or spherical bearing (cotter pin or snap ring type) ...13

Table 7 -- Dimensions of AP6 -- Rod eye spherical, female thread 14

Table 8 -- Dimensions of AP4 -- Rod eye plain, female thread 15