DIN ISO 6022:2008-06 (E)

Hydraulic fluid power - Mounting dimensions for single rod cylinders, 25 MPa (250 bar) series (ISO 6022:2006)

Contents

Page

National foreword 2

National Annex NA (informative) Bibliography 3

Introduction 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 6

4 Dimensions 6

5 Bore sizes 6

6 Mounting types 6

7 Piston rod characteristics 7

8 Identification statement (reference to this International Standard) 7

Bibliography 17

Figures Figure 1 -- General dimensions 8

Figure 2 -- MF3 -- Head, circular flange and MF 4 -- Cap, circular flange 10

Figure 3 -- MP3 -- Cap, fixed plain eye, MP4 -- Cap, detachable plain eye, MP5 -- Cap, fixed eye with spherical bearing and MP6 -- Cap, detachable eye with spherical bearing 12

Figure 4 -- MT4 -- Intermediate fixed or movable trunnion (male) 14

Tables Table 1 -- General dimensions 9

Table 2 -- Dimensions of circular flange mountings MF3 and MF4 11

Table 3 -- Dimensions of cap eye mountings MP3, MP4, MP5 and MP6 13

Table 4 -- Dimensions of intermediate male trunnion mounting MT4 14

Table 5 -- Port and flange sizes 15

Table 6 -- Tolerances for mounting dimensions that are dependent on stroke 16

Table 7 -- Tolerances on piston stroke 16