

DIN EN 474-12:2010-05 (E)

Earth-moving machinery - Safety - Part 12: Requirements for cable excavators (includes Amendment A1:2008)

Contents	Page
Foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms and definitions, symbols and abbreviated terms	7
4 List of additional significant hazards	7
5 Safety requirements and/or measures	7
5.1 General	7
5.2 Access	7
5.3 Operator's station	8
5.3.1 General	8
5.3.2 Roll-over protective structures (ROPS)	8
5.3.3 Operator's protective guard	8
5.3.4 Operator's seat, vibrations	8
5.4 Operator's controls and indicators	8
5.4.1 Controls for driving and steering	8
5.4.2 Warning indicator	8
5.5 Steering	8
5.6 Swing brakes	8
5.7 Lift system	9
5.7.1 Force controlled operation (lifting, lowering)	9
5.7.2 Free fall operation	9
5.7.3 Switch-over	9
5.7.4 Boom	9
5.7.5 Ropes	9
5.7.6 Rope drum, rope pulley	10
5.8 Limiting devices	10
5.8.1 Load moment limiting device	10
5.8.2 Lift limiting switch	10
5.8.3 Limit switch for the boom hoist system	10
5.9 Calculation of the lift capacity	10
5.9.1 Calculation method	10
5.9.2 Rated lift capacity table in object handling application	11
5.10 Requirements of safety related parts of the control system	11
5.11 Stability	11
5.11.1 General	11
5.11.2 Stability in different applications	11
5.11.3 Dragline bucket	11
5.11.4 Grab and front shovel	12
5.11.5 Object handling application	12
5.12 Cable excavator with electrical power source	12
6 Verification of safety requirements/measures	12
7 Information for use	12

7.1	Operation manual	12
B.3.1	Swing drive system	16
B.3.2	Swing service brake	16
B.3.3	Swing parking brake	17
B.4	Conditions for testing the swing service brake	17
B.5	Test report	17
Annex C (informative) Illustrations		18
C.1	Standard applications	18
C.1.1	Crawler type cable excavator with lifting equipment	18
C.1.2	Crawler type cable excavator with dragline equipment	19
C.1.3	Crawler type cable excavator with grab equipment	19
C.2	Special applications	20
C.2.1	Crawler type cable excavator with hole drilling equipment (casing oscillator)	20
C.2.2	Crawler type cable excavator with piling equipment (hydraulic or diesel hammer)	21
C.2.3	Crawler type excavator with wall cutter equipment (diaphragm wall grab)	21
C.3	Wheel type cable excavator in transport position for road travelling	22
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 98/37/EC		23
Annex ZB (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC		24
Bibliography		25
Figures Figure B.1 -- Swing service brake		16
Figure C.1.1 -- Crawler type cable excavator with lifting system		18
Figure C.1.2 -- Crawler type cable excavator with dragline equipment		19
Figure C.1.3 -- Crawler type cable excavator with grab equipment		19
Figure C.2.1 -- Crawler type excavator with hole drilling equipment (casing oscillator)		20
Figure C.2.2 -- Crawler type cable excavator with piling equipment (hydraulic or diesel hammer)		21
Figure C.2.3 -- Crawler type excavator with wall cutter equipment (diaphragm wall grab)		21
Figure C.3 -- Wheel type cable excavator in transport position for road travelling		22
Tables Table 1 -- Safety factors of ropes		9
Table A.1 -- List of additional significant hazards		14
Annex A (normative) List of additional significant hazards - Cable excavators		14
Annex B (normative) Requirements for cable excavator swing brakes		15
B.1	General	15
B.2	Terms and definitions	15
B.3	Minimum performance	16