

ISO/TR 18792:2008-12 (E)

Lubrication of industrial gear drives

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Terms and definitions	1
3	Basics of gear lubrication and failure modes	3
3.1	Tribo-technical parameters of gears	3
3.2	Gear lubricants	5
3.3	Base fluid components	6
3.4	Thickeners	8
3.5	Chemical properties of additives	9
3.6	Solid lubricants	10
3.7	Friction and temperature	10
3.8	Lubricating regime	11
3.9	Lubricant influence on gear failure	11
4	Test methods for lubricants	15
4.1	Gear tests	15
4.2	Other functional tests	16
5	Lubricant viscosity selection	19
5.1	Guideline for lubricant selection for parallel and bevel gears (not hypoid)	19
5.2	Guideline for lubricant selection for worm gears	24
5.3	Guideline for lubricant selection for open girth gears	24
6	Lubrication principles for gear units	26
6.1	Enclosed gear units	27
6.2	Open gearing	34
7	Gearbox service information	39
7.1	Initial lubricant fill and initial lubricant change period	39
7.2	Subsequent lubricant change interval	39
7.3	Recommendations for best practice for lubricant changes	40
7.4	Used gear lubricant sample analysis	41
	Bibliography	52
Figures		
	Figure 1 -- Load and speed distribution along the path of contact	4
	Figure 2 -- Scraping edge at the ingoing mesh	5
	Figure 3 -- Schematic diagram of shear effects on thickeners	9
	Figure 4 -- Mechanisms of surface protection for oils with additives	11

Figure 5 -- Examples of gear oil wear test results	15
Figure 6 -- Immersion of gear wheels	27
Figure 7 -- Immersion depth for different inclinations of the gearbox	29
Figure 8 -- Immersion of gear wheels in a multistage gearbox	30
Figure 9 -- Examples of circuit design, combination of filtration and cooling systems	34
Figure 10 -- Immersion lubrication	37
Figure 11 -- Transfer lubrication	37
Figure 12 -- Circulation lubrication	38
Figure 13 -- Automatic spraying lubrication	38
Tables	
Table 1 -- Symbols, indices and units	1
Table 1 (continued)	2
Table 2 -- General characteristics of base fluids	6
Table 3 -- Example of influence factors on wear	12
Table 4 -- Example of influence factors on scuffing load (transmittable torque)	13
Table 5 -- Example of influence factors on micropitting (transmittable torque)	14
Table 6 -- Example of influence factors on pitting (transmittable torque)	14
Table 7 -- ISO Viscosity grade1) at bulk oil operating temperature for oils having a viscosity index of 902)	20
Table 8 -- ISO Viscosity grade1) at bulk oil operating temperature for oils having a viscosity index of 1202)	21
Table 9 -- ISO Viscosity grade1) at bulk oil operating temperature for oils having a viscosity index of 1602)	22
Table 10 -- ISO Viscosity grade1) at bulk oil operating temperature for oils having a viscosity index of 2402)	23
Table 11 -- ISO viscosity grade guidelines for enclosed cylindrical worm gear drives	24
Table 12 -- Advantages and disadvantages of various open girth gears lubricants	25
Table 13 -- Minimum Viscosity recommendation for continuous lubrication [mm²/s at 40 °C]	26
Table 14 -- Minimum base oil viscosity recommendation for intermittent lubrication [mm²/s at 40 °C]	26
Table 15 -- Typical maximum oil flow velocities	33
Table 16 -- Advantages and disadvantages of greases	35
Table 17 -- Advantages and disadvantages of oils	35

Table 18 -- Advantages and disadvantages of lubricating compounds	36
Table 19 -- Lubrication system selection based on pitch line velocity	39
Table 20 -- Lubrication system selection based on the type of lubricant	39
Table 21 -- Typical recommended lubricant service	40
Table 22 -- Examples for an on-line oil condition-monitoring system	40
Table 23 -- Sources of metallic elements	47
Table 24 -- What the ISO codes mean	49
Table 25 -- Example of particle size and counts	49
Table 26 -- Characteristics of particles	51