DIN EN 1539:2010-08 (E)

Dryers and ovens, in which flammable substances are released - Safety requirements

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and Definitions 8

4 Significant hazards 12

5 Safety requirements and/or protective measures 17
5.1 General 17
5.2 Safety requirements against mechanical hazards 18
5.2.1 Shearing, crushing, drawing-in 18
5.2.2 Means of escape 18
5.2.3 Safety requirements against slip and fall hazards 19
5.3 Safety requirements against electrical hazards 19
5.3.1 General 19
5.3.2 Electrical equipment 19
5.3.3 External influences on the electrical equipment 19
5.4 Safety requirements against thermal hazards 19
5.5 Safety requirements against hazards from noise 20
5.6 Safety requirements against hazards from radiation 20
5.7 Safety requirements against hazards generated from hazardous substances 21
5.8 Fire protection and prevention 21
5.8.1 General 21
5.9 Explosion protection and prevention requirements 22
5.9.1 Type A-dryers 22
5.9.2 Type B-dryers 29
5.10 Control systems 31
5.11 Failure of energy supply 31

6 Verification of the safety requirements and/or measures 31

7 Information for use 34
7.1 General 34
7.2 Instruction handbook 34
7.2.1 General 34
7.2.2 Information related to installation 35
7.2.3 Information related to operation 35
7.2.4 Information related to maintenance and inspection 36
7.3 Marking 37

Annex A (normative) **Basis for air flow calculation of chamber dryers and continuous flow dryers** 38
A.1 Chamber dryers 38
A.1.1 Calculation basis for chamber dryers 38
A.2 Continuous flow dryers 43
A.2.1 Calculation basis for continuous flow dryers 43
A.2.2 Calculation basis for continuous flow dryers for powder coatings 45

Annex B (informative) **Examples of calculation** 46
B.1 Chamber dryers 46
B.1.1 Example 1: Calculation of the required minimum exhaust flow (see 3.20) 46
B.1.2 Example 2: Calculation of the maximum admissible amount of varnish 47
B.2 Continuous flow dryers 48

B.2.1 Examples for the calculation of the minimum exhaust flow rate 48
B.2.2 Example for the calculation of the maximum admissible throughput of flammable substances 50

Annex C (normative) **Concentration measurement in dryers 52**
C.1 General 52
C.2 Requirements for concentration measuring systems 52
C.3 Calculation of the lower explosion limit at drying temperature 53
C.3.1 Influence of temperature on the indicated value of concentration (physical influence) 53
C.3.2 Influence of the temperature of mixture on the kinetics of reaction (chemical influence) 54
C.3.3 Consideration of chemical and physical influences 54

Annex D (normative) **Explosion reliefs 55**

Annex ZA (informative) **Relationship between this European Standard and the Essential Requirements of EU Directive Machinery 98/37/EC 56**

Annex ZB (informative) **Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC 57**

Bibliography 58

Figures

Figure 1 — Maximum admissible concentration of flammable substances and admissible operating ranges for dryers with limited concentration 28

Figure A.1 — Dependency of γ versus τ 42

Tables

Table 1 — List of significant hazards 12

Table 2 — Requirements according to the operating ranges 27

Table 3 — Verification 32