DIN EN ISO 5801:2010-12 (E)

Industrial fans - Performance testing using standardized airways (ISO 5801:2007, including Cor 1:2008)

Contents

Page

Foreword 6

Introduction .....

1 Scope 9

2 Normative references 9

3 Terms and definitions 9

4 Symbols and units 24
4.1 Symbols 24
4.2 Subscripts 27

5 General 27

6 Instruments for pressure measurement 28
6.1 Barometers 28
6.2 Manometers 29
6.3 Damping of manometers 29
6.4 Checking of manometers 29
6.5 Position of manometers 30

7 Determination of average pressure in an airway 30
7.1 Methods of measurement 30
7.2 Use of wall tappings 30
7.3 Construction of tappings 30
7.4 Position and connections 31
7.5 Checks for compliance 31
7.6 Use of Pitot-static tube 31

8 Measurement of temperature 32
8.1 Thermometers 32
8.2 Thermometer location 32
8.3 Humidity 32

9 Measurement of rotational speed 33
9.1 Fan shaft speed 33
9.2 Acceptable instruments 33

10 Determination of power input 33
10.1 Measurement accuracy 33
10.2 Fan shaft power 33
10.3 Determination of fan shaft power by electrical measurement 33
10.4 Impeller power 34
10.5 Transmission systems 34

11 Measurement of dimensions and determination of areas 34
11.1 Flow-measurement devices 34
11.2 Tolerance on dimensions 34
11.3 Determination of cross-sectional area 35

12 Determination of air density, humid gas constant and viscosity 35
12.1 Density of air in the test enclosure at section x 35
12.2 Determination of vapour pressure 36
12.3 Determination of air viscosity 38

13 Determination of flow rate 39
13.1 General 39
13.2 In-line flowmeters (standard primary devices) 39
13.3 Traverse methods 40

14 Calculation of test results 42
14.1 General 42
14.2 Units 42
14.3 Temperature 42
14.4 Mach number and reference conditions 44
14.5 Fan pressure 48
14.6 Calculation of stagnation pressure at a reference section of the fan from gauge pressure, pex, measured at a section x of the test duct 51
14.7 Inlet volume flow rate 52
14.8 Fan air power and efficiency 52

15 Rules for conversion of test results 60
15.1 Laws on fan similarity 60
15.2 Conversion rules 62

16 Fan characteristic curves 65
16.1 General 65
16.2 Methods of plotting 66
16.3 Characteristic curves at constant speed 66
16.4 Characteristic curves at inherent speed 66
16.5 Characteristic curves for adjustable-duty fan 67
16.6 Complete fan characteristic curve 68
16.7 Test for a specified duty 69

17 Uncertainty analysis 70
17.1 Principle 70
17.2 Pre-test and post-test analysis 70
17.3 Analysis procedure 70
17.4 Propagation of uncertainties 70
17.5 Reporting uncertainties 71
17.6 Maximum allowable uncertainties measurement 71
17.7 Maximum allowable uncertainty of results 72

18 Selection of test method 73
18.1 Classification 73
18.2 Installation categories 73
18.3 Test report 73
18.4 User installations 74
18.5 Alternative methods 74
18.6 Duct simulation 74

19 Installation of fan and test airways 74
19.1 Inlets and outlets 74
19.2 Airways 74
19.3 Test enclosure 75
19.4 Matching fan and airway 75
19.5 Outlet area 75

20 Carrying out the test 75
20.1 Working fluid 75
20.2 Rotational speed 75

20.3 Steady operation 75
20.4 Ambient conditions 76
20.5 Pressure readings 76
20.6 Tests for a specified duty 76
20.7 Tests for a fan characteristic curve 76
20.8 Operating range 76

21 Determination of flow rate 76
21.1 Multiple nozzle 76
21.2 Conical or bellmouth inlet 76
21.3 Orifice plate 76
21.4 Pilot-static tube traverse (see ISO 3966 and ISO 5221) 77

22 Determination of flow rate using multiple nozzles 77
22.1 Installation 77
22.2 Geometric form 77
22.3 Inlet zone 78
22.4 Multiple-nozzle characteristics 78
22.5 Uncertainty 80

23 Determination of flow rate using a conical or bellmouth inlet 81
23.1 Geometric form 81
23.2 Screen loading 82
23.3 Inlet zone 83
23.4 Conical inlet performance 83
23.5 Bellmouth inlet performance 83
23.6 Uncertainties 85

24 Determination of flow rate using an orifice plate 85
24.1 Installation 85
24.2 Orifice plate 85
24.3 Ducts 89
24.4 Pressure tappings 89
24.5 Calculation of mass flow rate 89
24.6 Reynolds number 90
24.7 In-duct orifice with D and D/2 taps [see Figure 20 a) and ISO 5167-1] 90
24.8 Outlet orifice with wall tappings [see Figure 20 c) and e)] 94

25 Determination of flow rate using a Pitot-static tube traverse 96
25.1 General 96
25.2 Pitot-static tube 96
25.3 Limits of air velocity 101
25.4 Location of measurement points 101
25.5 Determination of flow rate 102
25.6 Flow rate coefficient 102
25.7 Uncertainty of measurement 103

26 Installation and setup categories 103
26.1 Category A: free inlet and free outlet 103
26.2 Category B: free inlet and ducted outlet 103
26.3 Category C: ducted inlet and free outlet 104
26.4 Category D: ducted inlet and ducted outlet 104
26.5 Test installation type 104

27 Flow straighteners 104
27.1 Types of straightener 105
27.2 Rules for use of a straightener 106

28 Common-segment airways for ducted fan installations 107
28.1 Common segments 107
28.2 Common segment at fan outlet 107
28.3 Common segment at fan inlet 109

28.4 Outlet duct simulation 111
28.5 Inlet duct simulation 111
28.6 Loss allowances for standardized airways 112

29 Standardized test chambers 115
29.1 Test chamber 115
29.2 Variable supply and exhaust systems 120
29.3 Standardized inlet test chambers 120
29.4 Standardized outlet test chambers 123

30 Standard methods with test chambers -- Category A installations 126
30.1 Types of fan setup 126
30.2 Inlet-side test chambers 126
30.3 Outlet-side test chambers 139

31 Standard test methods with outlet-side test ducts -- Category B installations 144
31.1 Types of fan setup 144
31.2 Outlet-side test ducts with antiswirl device 145
31.3 Outlet chamber test ducts without antiswirl device 157

32 Standard test methods with inlet-side test ducts or chambers -- Category C installations 164
32.1 Types of fan setup 164
32.2 Inlet-side test ducts 165
32.3 Inlet-side test chambers 178

33 Standard methods with inlet- and outlet-side test ducts -- Category D installations 188
33.1 Types of fan setup 188
33.2 Installation category B with outlet antiswirl device and with an additional inlet duct or inlet-duct simulation 192
33.3 Installation category B without outlet antiswirl device nor common segment, modified with addition of an inlet duct or inlet-duct simulation 198
33.4 Installation category C with common inlet duct, modified with the addition of an outlet common segment with antiswirl device 201
33.5 Installation category C, modified with the addition of an outlet-duct simulation without antiswirl device 205

Annex A (normative) Fan pressure and fan installation category 213

Annex B (normative) Fan-powered roof exhaust ventilators 217

Annex C (informative) Chamber leakage test procedure 219

Annex D (informative) Fan outlet elbow in the case of a non-horizontal discharge axis 225

Annex E (informative) Electrical input power consumed by a fan installation 228

Annex F (informative) Preferred methods of performance testing 235

Bibliography 236