

# ISO 14223-2:2010-08 (E)

## Radiofrequency identification of animals - Advanced transponders - Part 2: Code and command structure

---

| <b>Contents</b>    |  | <b>Page</b> |
|--------------------|--|-------------|
| Foreword .....     |  | v           |
| Introduction ..... |  | vi          |
| <b>1</b>           | <b>Scope .....</b>                                   | <b>1</b>    |
| <b>2</b>           | <b>Normative references .....</b>                    | <b>1</b>    |
| <b>3</b>           | <b>Conformance .....</b>                             | <b>1</b>    |
| 3.1                | Transponder .....                                    | 1           |
| 3.2                | Transceiver .....                                    | 1           |
| <b>4</b>           | <b>Terms and definitions .....</b>                   | <b>2</b>    |
| <b>5</b>           | <b>Abbreviated terms .....</b>                       | <b>2</b>    |
| <b>6</b>           | <b>Transmission protocol .....</b>                   | <b>3</b>    |
| 6.1                | Basic elements .....                                 | 3           |
| 6.2                | Unique identifier .....                              | 3           |
| 6.3                | Request format .....                                 | 4           |
| 6.4                | Response format .....                                | 5           |
| 6.5                | Request flags .....                                  | 5           |
| 6.5.1              | General .....  | 5           |
| 6.5.2              | NOS flag .....                                       | 6           |
| 6.5.3              | SEL flag and ADR flag .....                          | 7           |
| 6.5.4              | CRCT flag .....                                      | 7           |
| 6.6                | Response flag and error code .....                   | 7           |
| 6.7                | Error handling .....                                 | 8           |
| 6.8                | Block security status (BSS) .....                    | 8           |
| 6.9                | Start of frame pattern (SOF) .....                   | 9           |
| 6.9.1              | Transceiver request .....                            | 9           |
| 6.9.2              | Transponder response .....                           | 9           |
| 6.10               | Cyclic redundancy check (CRC) .....                  | 9           |
| 6.11               | Data storage format identifier (DSFID) .....         | 9           |
| <b>7</b>           | <b>Memory organization .....</b>                     | <b>10</b>   |
| 7.1                | General .....  | 10          |
| 7.2                | User data memory -- Page 0 .....                     | 10          |
| 7.3                | User data memory -- Extended memory (W page 1) ..... | 10          |
| <b>8</b>           | <b>Transponder states .....</b>                      | <b>11</b>   |
| 8.1                | General .....  | 11          |
| 8.2                | RF-off state .....                                   | 11          |
| 8.3                | ISO 11785 state .....                                | 11          |
| 8.4                | Wait state .....                                     | 11          |
| 8.5                | Ready state .....                                    | 11          |
| 8.6                | Quiet state .....                                    | 11          |
| 8.7                | Selected state .....                                 | 11          |
| 8.8                | State diagram .....                                  | 12          |
| <b>9</b>           | <b>Anticollision .....</b>                           | <b>13</b>   |

|   |  |    |
|---|--|----|
| 9.1   | General .....  | 13 |
| 9.2   | Request parameters .....   | 13 |
| 9.3   | Request processing by the transponder .....                          | 14 |
| 9.4   | Explanation of anticollision sequences .....                         | 16 |
| 9.4.1   | General .....  | 16 |
| 9.4.2   | Anticollision sequence with one slot .....                           | 16 |
| 9.4.3   | Anticollision sequence with 16 slots .....                           | 16 |
| 9.4.4   | Mixed population with transponders of type FDX-ADV and HDX-ADV ..... | 17 |
| 9.4.5   | Advanced anticollision mode .....                                    | 17 |
| 10  | Commands .....   | 19 |
| 10.1  | Command classification .....   | 19 |
| 10.2  | Command list .....   | 20 |
| 10.3  | Mandatory commands .....   | 21 |
| 10.3.1  | INVENTORY .....  | 21 |
| 10.3.2  | READ UID .....   | 22 |
| 10.3.3  | READ MULTIPLE BLOCKS .....   | 22 |
| 10.3.4  | STAY QUIET .....   | 23 |
| 10.3.5  | WRITE SINGLE BLOCK .....   | 23 |
| 10.3.6  | LOCK BLOCK .....   | 23 |
| 10.4  | Optional commands .....  | 24 |
| 10.4.1  | READ SINGLE BLOCK .....  | 24 |
| 10.4.2  | READ SINGLE BLOCK WITH SECURITY STATUS .....                         | 24 |
| 10.4.3  | READ MULTIPLE BLOCKS WITH SECURITY STATUS .....                      | 25 |
| 10.4.4  | WRITE MULTIPLE BLOCKS .....  | 25 |
| 10.4.5  | GET SYSTEM INFORMATION .....   | 26 |
| 10.4.6  | SELECT .....   | 27 |
| 10.4.7  | RESET TO READY .....   | 28 |
| 10.4.8  | WRITE SYSTEM DATA .....  | 28 |
| 10.4.9  | LOCK SYSTEM DATA .....   | 29 |
| 10.4.10   | READ EXTENDED MULTIPLE BLOCKS .....                                  | 29 |
| 10.4.11   | WRITE EXTENDED MULTIPLE BLOCKS .....                                 | 30 |
| 10.4.12   | LOCK EXTENDED BLOCK .....  | 31 |
| 10.4.13   | Optional command execution in inventory mode .....                   | 31 |
| 10.5  | Custom commands .....  | 32 |
| 10.6  | Proprietary commands .....   | 32 |
| Annex A (informative) Description of a typical anticollision sequence with FDX and HDX transponders ..... |  | 33 |
| Bibliography .....  |  | 34 |