DIN 743-1:2012-12 (E)

Calculation of load capacity of shafts and axles - Part 1: General

Contents

Page

Foreword 3

Introduction 5

1 Scope 6

2 Normative references 7

3 Symbols, designations and units 7

4 Proof of avoidance of fatigue failure 9
4.1 Factor of safety 9
4.2 Working stresses 10
4.3 Fatigue strength value 10

5 Proof of avoidance of permanent deformation, incipient cracking or overload breakage under maximum load 14
5.1 Safety factor 14
5.1.1 Proof of avoidance of permanent deformation 15
5.1.2 Proof of avoidance of incipient cracking (and/or overload breakage) in hard surfaces 16
5.2 Component yield point 16
5.3 Component's incipient crack limit 17
5.4 Working stresses (maximum stresses) 18

Annex A (informative) Explanations of the variation of load and/or stress, cross-sectional areas and the reading of σ_{ADK} from the Smith diagram 19

Annex B (normative) Schema of the safety factor calculation 22

B.1 General schema 22
B.2 Total influence factor 24

Bibliography 25

Figures

Figure A.1 — Variation of applied load with time ($F_{zd,}$ $M_{b,}$ M_t) and stress ($\sigma_{zd,}$ $\sigma_{b,}$ τ_t) 19

Figure A.2 — Origination of amplitude of bending moment M_b as a result of shaft rotation (rotational bending); force F with constant direction, shaft rotating $(\omega = 2 \cdot \pi \cdot n > 0)$ 19

Figure A.3 — Cross section parameters 19

Figure A.4 — Load cases, represented in the fatigue strength diagram (Smith diagram) 20

Figure A.5 — Fatigue strength diagram with extension of the compression zone (component pressure yield point σ_{dFK}) 21

Figure B.1 — Calculation procedure for safety factors 23

Figure B.2 — Calculation procedure for total influence factor $K_{\sigma,\tau}$ 24

Tables

Table 1 — Determination of working stresses 10

Table 2 — Increase factor for yield point γ_F at circumferential notch (α_σ and/or β_σ according to DIN 743-2) and materials without hard surface 17

Table 3 — Static support factor K_{2F} for materials without hard surface 17

Table 4 — Determination of maximum stresses (maximum nominal stresses) 18

Table A1 — σ_{ADK} in the marked compression zone for load case 1 with $\sigma_{mv} < \sigma_{mv\ grenz\ F1}$ and/or for load case 2 with $\sigma_{mv}/\sigma_a < (\sigma_{mv}/\sigma_a)_{grenz\ F2}$ (in the compression zone $\sigma_{mv} < 0$ or $\sigma_{mv}/\sigma_a < 0$ applies) 21