

# DIN 743-2:2012-12 (E)

## Calculation of load capacity of shafts and axles - Part 2: Theoretical stress concentration factors and fatigue notch factors

---

| <b>Contents</b>    |   | <b>Page</b> |
|--------------------|---|-------------|
| 1                  | Scope .....   | 5           |
| 2                  | Normative references .....  | 5           |
| 3                  | Symbols, designations and units.....  | 5           |
| 4                  | Fatigue notch factor .....  | 6           |
| 4.1                | Definition of fatigue notch factor .....  | 6           |
| 4.2                | Experimentally determined fatigue notch factors .....                                     | 6           |
| 4.2.1              | Parallel keyway and interference fit.....   | 6           |
| 4.2.2              | Fatigue notch factors for splined shafts, serrated shafts and involute spline shafts..... | 8           |
| 4.2.3              | Fatigue notch factors for round bars with V-notch.....                                    | 10          |
| 4.2.4              | Fatigue notch factors for circumferential rectangular notch.....                          | 11          |
| 4.3                | Fatigue notch factors for notches with known stress concentration factor .....            | 12          |
| 4.3.1              | Shoulder, U-notch, shoulder with undercut, transverse hole .....                          | 12          |
| 4.3.2              | Notch cases not yet dealt with .....  | 14          |
| 5                  | Stress concentration factors .....  | 14          |
| 5.1                | Definition of stress concentration factor .....   | 14          |
| 5.2                | Stress concentration factors for different notch shapes .....                             | 15          |
| 5.2.1              | Shoulder and U-notch .....  | 15          |
| 5.2.2              | Shoulder with undercut.....   | 22          |
| 5.2.3              | Transverse hole .....   | 23          |
| 6                  | Size influence factors .....  | 24          |
| 6.1                | General information.....  | 24          |
| 6.2                | Technological size influence factor $K_1(d_{\text{eff}})$ .....                           | 24          |
| 6.3                | Geometrical size influence factor $K_2(d)$ .....  | 26          |
| 6.4                | Geometrical size influence factor $K_3(d)$ .....  | 27          |
| 7                  | Influence factor for surface roughness $K_{F\sigma,\tau}$ .....                           | 28          |
| 8                  | Influence factor for surface conditioning $K_V$ .....                                     | 30          |
| Bibliography ..... |   | 34          |

### Figures

|   |    |
|---|----|
| Figure 1— Fatigue notch factors for splined shafts, serrated shafts and involute spline shafts .....  | 8  |
| Figure 2 — Fatigue notch factors for round bars with circumferential V-notch [2].....   | 10 |
| Figure 3 — Circumferential rectangular notch for circlips according to DIN 471 and structural radius $\rho^*$ according to Neuber [9] ..... | 11 |
| Figure 4 — Sensitivity factor $n$ .....   | 13 |
| Figure 5 — Stress concentration factors for notched round bars in tension .....   | 16 |
| Figure 6 — Stress concentration factors for notched round bars in bending .....   | 17 |
| Figure 7 — Stress concentration factors for notched round bars in torsion .....   | 18 |
| Figure 8 — Stress concentration factors for shouldered round bars in tension.....   | 19 |
| Figure 9 — Stress concentration factors for shouldered round bars in bending.....   | 20 |
| Figure 10 — Stress concentration factors for shouldered round bars in torsion .....   | 21 |

|  |           |
|--|-----------|
| <b>Figure 11 — Shoulder with undercut.....</b>   | <b>22</b> |
| <b>Figure 12 — Stress concentration factors for round bars with transverse hole in tension/<br/>compression, bending or torsion (tension/compression [2], bending and torsion [1]) .....</b> | <b>23</b> |
| <b>Figure 13 — Technological size influence factor <math>K_1(d_{\text{eff}})</math> .....</b>  | <b>25</b> |
| <b>Figure 14 — Geometrical size influence factor <math>K_2(d)</math> .....</b>   | <b>26</b> |
| <b>Figure 15 — Geometrical size influence factor <math>K_3(d)</math> .....</b>   | <b>27</b> |
| <b>Figure 16 — Influence factor for surface roughness <math>K_{FO}</math>.....</b>   | <b>29</b> |
| <b>Figure 17 — Influence factor for surface conditioning, <math>K_V</math>, in chemico-thermal processes .....</b>   | <b>31</b> |
| <b>Figure 18 — Influence factor for surface conditioning, <math>K_V</math>, in mechanical processes .....</b>  | <b>32</b> |
| <b>Figure 19 — Influence factor for surface conditioning, <math>K_V</math>, in thermal processes .....</b>   | <b>32</b> |
| <b>Tables</b>  |           |
| <b>Table 1 — Fatigue notch factors <math>\beta_{\sigma,\tau}(d_{BK})</math> for shaft-hub connections .....</b>  | <b>7</b>  |
| <b>Table 2 — Relative stress gradient <math>G'</math>.....</b>   | <b>14</b> |
| <b>Table 3 — Stress concentration factor constants <math>A, B, C</math> and exponent <math>z</math>.....</b>   | <b>15</b> |
| <b>Table 4 — Influence factor for surface conditioning, <math>K_V</math>, as a function of the<br/>technological process; guidance values .....</b>  | <b>33</b> |