

DIN EN 15830:2012-08 (E)

Rough-terrain variable reach trucks - Visibility - Test methods and verification

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Basic dimensions | 10 |
| 4.1 | Light bulb spacing dimensions | 10 |
| 4.2 | Masking dimensions | 10 |
| 4.3 | Reference dimensions for the measurement | 10 |
| 5 | Test apparatus | 11 |
| 5.1 | Test load | 11 |
| 5.2 | Light source apparatus | 11 |
| 5.3 | Vertical test object | 11 |
| 5.4 | Observation mirror | 11 |
| 6 | Truck test configuration | 11 |
| 6.1 | Equipment of the truck | 11 |
| 6.2 | Openings | 12 |
| 6.3 | Position of the truck and load handling attachment | 12 |
| 6.3.1 | General | 12 |
| 6.3.2 | Tests in normal travel mode | 12 |
| 6.3.3 | Tests with suspended load | 13 |
| 6.3.4 | Lorry trailer loading condition | 14 |
| 7 | Measurement procedure | 14 |
| 7.1 | Test-surface marking and truck location on the test surface | 14 |
| 7.2 | Positioning of the test apparatus | 15 |
| 7.3 | Measurement of the masking | 16 |
| 7.3.1 | General | 16 |
| 7.3.2 | Measurement at the visibility test circle | 16 |
| 7.3.3 | Measurement at the rectangular 1 m boundary | 16 |
| 7.4 | Fork arm visibility | 17 |
| 7.5 | Requirements for derivative trucks | 18 |
| 8 | Calculation method and computer simulation | 18 |
| 8.1 | Calculation method | 18 |
| 8.2 | Computer simulation | 18 |
| 9 | Evaluation method and performance criteria | 18 |
| 9.1 | Visibility performance criteria on the visibility test circle | 18 |
| 9.2 | Visibility performance criteria for the rectangular 1 m boundary | 19 |
| 9.3 | Visibility masking that exceed the visibility performance criteria with direct view | 23 |
| 9.4 | Fork arm visibility criteria | 23 |
| 10 | Test reports | 23 |
| 10.1 | Truck details | 23 |

| | | |
|-------------|---|-----------|
| 10.2 | Drawing | 23 |
| 11 | Information for use | 23 |
| | Annex A (normative) Light bulb spacing dimensions | 25 |
| | Annex B (informative) Performance criteria for additional devices | 26 |
| B.1 | Performance criteria for mirrors | 26 |
| B.2 | Performance criteria for CCTV system | 26 |
| | Annex C (informative) Procedure for the determination of masking at the visibility test circle or the rectangular 1 m boundary | 27 |
| | Annex D (informative) Examples of drawings for the test report | 28 |
| | Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC | 30 |
| | Bibliography | 31 |