DIN EN 16297-1:2013-04 (E)

Pumps - Rotodynamic pumps - Glandless circulators - Part 1: General requirements and procedures for testing and calculation of energy efficiency index (EEI)

Contents

Page

Foreword 3

Introduction 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Symbols and units 9

5 Performance requirements and safety requirements 9
5.1 Hydraulic characteristics 9
5.1.1 General 9
5.1.2 Q100% and H100% 10
5.2 Rated and minimum power input 10
5.3 Starting characteristics 10
5.4 Resistance to internal pressure 10
5.5 Resistance to thermal cycling 10
5.6 Venting and deblocking 10
5.7 Fluid and structure borne noise emission 10

6 General test methods 10
6.1 General 10
6.2 Testing of the hydraulic characteristic 11
6.2.1 Rated hydraulic output power, Phyd,r 11
6.2.2 Reference power, Pref 12
6.2.3 Tolerance on H100% at maximum hydraulic power 12
6.2.4 Reference control curve 13
6.2.5 Load profile for calculation of average compensated power input, PLavg 13
6.2.6 Part load operating points 13
6.2.7 Calculation of compensated power input, PL 16
6.2.8 Calculation of average compensated power input, PL,avg 16
6.2.9 Calculation of energy efficiency index (EEI), EEI 16
6.2.10 Test conditions 17
6.2.11 Testing of hydraulic performance 18
6.3 Measurement of rated power input 18
6.4 Starting conditions 18
6.5 Testing of resistance to internal pressure 19
6.6 Testing of resistance to thermal cycling 19
6.6.1 Circulator supply voltage 19
6.6.2 Intermittent operation 19

7 Information for use 20
7.1 General 20
7.2 Instruction handbook 20
7.3 Marking 20

Annex ZA (informative) Relationship between this European Standard and the requirements of Commission Regulation (EC) No 641/2009 21

Bibliography 22