

ISO 15619:2013-10 (E)

Reciprocating internal combustion engines - Measurement method for exhaust silencers - Sound power level of exhaust noise and insertion loss using sound pressure and power loss ratio

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
1.1	Measurement uncertainty	1
2	Normative references	2
3	Terms and definitions	2
4	Test environment	6
4.1	General	6
4.2	Criteria for background noise	7
4.3	Criterion for acoustic adequacy of test environment	9
5	Instrumentation	10
5.1	General	10
5.2	Calibration	10
6	Installation and operation of noise source under test for laboratory measurement	10
6.1	General	10
6.2	Source location	11
6.3	Installation requirements	11
6.4	Operation condition	13
7	Measurement	13
7.1	General	13
7.2	Laboratory measurement	14
7.3	Site measurement	17
8	Calculation	20
8.1	General	20
8.2	Calculation of sound power level of exhaust noise	20
8.3	Calculation of insertion loss	22
8.4	Calculation of power loss ratio	23
9	Information to be recorded	23
9.1	General	23
9.2	Description of the tested exhaust silencer and substitution pipe	23
9.3	Description of the engine on which the exhaust silencer is installed	23
9.4	Acoustic environment	23
9.5	Description of instrumentation	23
9.6	Acoustical data	23
10	Test report	24
Annex A (normative)	Qualification procedures for the acoustic environment	25

Annex B (informative) Measurement procedure for pressure loss	30
Annex C (normative) Calculation of A-weighted sound power levels from frequency band levels	31
Annex D (normative) Sound power level under reference meteorological conditions	33
Bibliography	35