

# DIN ISO 21771:2014-08 (E)

## Gears - Cylindrical involute gears and gear pairs - Concepts and geometry (ISO 21771:2007)

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>9</b>
<b>2</b>	<b>Normative references .....</b>	<b>9</b>
<b>3</b>	<b>Symbols, subscripts and units .....</b>	<b>10</b>
<b>3.1</b>	<b>Symbols .....</b>	<b>10</b>
<b>3.2</b>	<b>Subscripts .....</b>	<b>16</b>
<b>3.3</b>	<b>Units .....</b>	<b>17</b>
<b>4</b>	<b>Individual cylindrical gears .....</b>	<b>18</b>
<b>4.1</b>	<b>Concepts for an individual gear .....</b>	<b>18</b>
<b>4.2</b>	<b>Reference surfaces, datum lines and reference quantities .....</b>	<b>20</b>
<b>4.3</b>	<b>Involute helicoids .....</b>	<b>25</b>
<b>4.4</b>	<b>Angular pitch and pitches .....</b>	<b>29</b>
<b>4.5</b>	<b>Diameters of gear teeth .....</b>	<b>32</b>
<b>4.6</b>	<b>Gear tooth height .....</b>	<b>32</b>
<b>4.7</b>	<b>Tooth thickness, space width .....</b>	<b>33</b>
<b>5</b>	<b>Cylindrical gear pairs .....</b>	<b>35</b>
<b>5.1</b>	<b>Concepts for a gear pair .....</b>	<b>35</b>
<b>5.2</b>	<b>Mating quantities .....</b>	<b>36</b>
<b>5.3</b>	<b>Calculation of the sum of the profile shift coefficients .....</b>	<b>39</b>
<b>5.4</b>	<b>Tooth engagement .....</b>	<b>40</b>
<b>5.5</b>	<b>Backlash .....</b>	<b>48</b>
<b>5.6</b>	<b>Sliding conditions at the tooth flanks .....</b>	<b>49</b>
<b>6</b>	<b>Tooth flank modifications .....</b>	<b>52</b>
<b>6.1</b>	<b>Tooth flank modifications which restrict the usable flank .....</b>	<b>52</b>
<b>6.2</b>	<b>Transverse profile modifications .....</b>	<b>53</b>
<b>6.3</b>	<b>Flank line (helix) modifications .....</b>	<b>56</b>
<b>6.4</b>	<b>Flank face modifications .....</b>	<b>57</b>
<b>6.5</b>	<b>Descriptions of modifications by functions .....</b>	<b>59</b>
<b>7</b>	<b>Geometrical limits .....</b>	<b>60</b>
<b>7.1</b>	<b>Counterpart rack tooth profile .....</b>	<b>61</b>
<b>7.2</b>	<b>Machining allowance .....</b>	<b>62</b>
<b>7.3</b>	<b>Deviations in tooth thickness .....</b>	<b>63</b>
<b>7.4</b>	<b>Generating profile shift, generating profile shift coefficient .....</b>	<b>64</b>
<b>7.5</b>	<b>Generated root diameter .....</b>	<b>65</b>
<b>7.6</b>	<b>Usable area of the tooth flank, tip and root form diameter .....</b>	<b>65</b>
<b>7.7</b>	<b>Undercut .....</b>	<b>67</b>
<b>7.8</b>	<b>Overcut .....</b>	<b>67</b>
<b>7.9</b>	<b>Minimum tooth thickness at the tip circle of a gear .....</b>	<b>67</b>
	<b>Annex A (informative) Calculations related to tooth thickness .....</b>	<b>68</b>
	<b>Bibliography .....</b>	<b>91</b>
	<b>National foreword .....</b>	<b>3</b>
	<b>National Annex NA (informative) Bibliography .....</b>	<b>4</b>
	<b>National Annex NB (normative) Corrections .....</b>	<b>5</b>