

ISO 10300-2:2014-04 (E)

Calculation of load capacity of bevel gears - Part 2: Calculation of surface durability (pitting)

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols, units and abbreviated terms	2
5	Pitting damage -- General aspects	3
5.1	Acceptable versus unacceptable pitting	3
5.2	Assessment requirements	3
5.3	General rating procedure	4
6	Gear flank rating formulae -- Method B1	4
6.1	Contact stress formula	4
6.2	Permissible contact stress	6
6.3	Calculated safety factor for contact stress	6
6.4	Contact stress factors	6
6.5	Permissible contact stress factors	10
7	Gear flank rating formulae -- Method B2	13
7.1	Contact stress formula	13
7.2	Permissible contact stress	14
7.3	Calculated safety factor for contact stress	14
7.4	Contact stress factors	15
8	Factors for contact stress and permissible contact stress common for method B1 and method B2	20
8.1	Elasticity factor, Z_E	20
8.2	Lubricant film influence factors, Z_L , Z_V , Z_R	20
8.3	Work hardening factor, Z_W	24
8.4	Life factor, Z_{NT}	25
Annex A (informative)	Bevel slip factor Z_S -- Method B1	28
Bibliography		30