

DIN EN 16644:2015-04 (E)

Pumps - Rotodynamic pumps - Glandless circulators having a rated power input not exceeding 200 W for heating installations and domestic hot water installations - Noise test code (vibro-acoustics) for measuring structure- and fluid-borne noise

Contents	Page
Foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
4 Symbols and units	8
5 Test rig	8
5.1 General	8
5.2 Main components of test rig	8
5.3 Specification of test rig components	10
5.4 Assembly	13
5.5 Foundation	13
5.6 Qualifications	13
5.7 Instrumentation	13
5.7.1 Measurement of pressure fluctuations	13
5.7.2 Measurement of vibration	13
5.8 Calibration	14
5.8.1 Accelerometers	14
5.8.2 Pressure transducers	14
5.8.3 Calibration of accelerometers and pressure transducers	14
5.9 Propagation coefficients	14
6 Installation and operation	15
6.1 Installation	15
6.2 Operating parameters	16
6.2.1 General	16
6.2.2 Test conditions	16
6.3 Initial operation time	17
7 Factors influencing measurements	17
7.1 Electromagnetic surroundings	17
7.2 Earth loops	17
7.3 Vibration surroundings	18
8 Determination of fluid- and structure-borne powers	18
8.1 Frequency range	18
8.2 Measurement parameters	18
8.2.1 Pressure fluctuation measurement parameters	18
8.2.2 Vibration measurement parameters	18
8.3 Sense of power propagation	19
8.4 Fluid-borne power determination	19
8.4.1 General	19
8.4.2 Fluid-borne intensity	19

8.4.3	Fluid-borne power	20
8.5	Structure-borne power determination	20
8.5.1	General	20
8.5.2	Structure-borne intensity	20
8.5.3	Structure-borne power	21
8.6	Overall values of power	21
8.7	Coefficients of energy propagation and power levels	21
8.7.1	Coefficient of fluid-borne energy propagation	21
8.7.2	Coefficient of structure-borne energy propagation	21
8.7.3	Fluid-borne power level	22
8.7.4	Structure-borne power level	22
9	Information to be reported	22
	Annex A (informative) Bending wave number and intensity dimensional constant	23
	Bibliography	25