

ISO 6358-3:2014-10 (E)

Pneumatic fluid power - Determination of flow-rate characteristics of components using compressible fluids - Part 3: Method for calculating steady-state flow-rate characteristics of systems

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and units	1
5	Calculation hypotheses	2
5.1	General	2
5.2	Relationships among component flow-rate characteristics	3
5.3	Flow-rate characteristics	3
6	Organization of calculations for systems of components connected in series	6
6.1	General	6
6.2	Given parameters	7
6.3	Calculation principle	7
6.4	Calculation of the cracking pressure p_c (step 1)	7
6.5	Calculation of an initial value for their sonic conductance if some components are pipes, tubes or hoses defined by their friction factor (optional step 2)	7
6.6	Determination of the sonic conductance C (step 3)	8
6.7	Determining the critical back-pressure ratio b and subsonic index m (step 4)	10
6.8	Calculation of pressure dependence coefficient K_p (optional step 5)	11
7	Organization of calculations for systems of components connected in parallel	12
7.1	General	12
7.2	Given parameters	12
7.3	Calculation principle	12
7.4	Determination of flow characteristics of pipes, tubes or hoses for the given inlet pressure (step 0)	13
7.5	Determination of the sonic conductance C (step 1)	13
7.6	Determination of the cracking pressure p_c (step 2)	13
7.7	Determination of the critical back-pressure ratio b and subsonic index m (step 3)	13
	Annex A (informative) Example calculation for a system of components connected in series	15
	Annex B (informative) Example calculation for an air blow circuit whose components are connected in parallel	25
	Annex C (informative) Flow charts of calculation procedures	32
	Annex D (informative) Additional information concerning components whose flow rate characteristics are not expressed in accordance with the ISO 6358 series	41
	Annex E (informative) Visualization of calculation results	53
	Bibliography	59