

# ISO 6953-1:2015-03 (E)

## Pneumatic fluid power - Compressed air pressure regulators and filter-regulators - Part 1: Main characteristics to be included in literature from suppliers and product-marking requirements

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Technical requirements .....</b>	<b>2</b>
4.1	General .....	2
4.2	General characteristics .....	3
4.2.1	General dimensions .....	3
4.2.2	Port forms .....	5
4.2.3	Rated pressure .....	5
4.2.4	Range of operating temperatures .....	5
4.3	Particular requirements .....	5
4.3.1	General .....	5
4.3.2	Adjustable pressure ranges (outlet regulated pressure) .....	5
4.3.3	Flow-pressure characteristics .....	6
4.3.4	Pressure regulation characteristic .....	7
4.3.5	Pilot pressure/regulated pressure characteristics .....	7
4.3.6	Repeatability (optional characteristic) .....	9
4.3.7	Resolution in the case of pilot operated regulator with air bleed .....	9
4.3.8	Maximum air consumption at null forward flow rate or relief flow rate for pilot operated regulator with air bleed .....	9
4.3.9	Useful retention capacity of the reservoir .....	9
4.3.10	Filter-regulator draining devices .....	9
4.3.11	Materials of construction .....	9
<b>5</b>	<b>Operation and maintenance .....</b>	<b>10</b>
<b>6</b>	<b>Marking .....</b>	<b>10</b>
Annex A (informative)	Port forms from ISO 1179-1:1981 .....	11
Bibliography .....		12