ISO 16122-4:2015-03 (E)

Agricultural and forestry machines - Inspection of sprayers in use - Part 4: Fixed and semi-mobile sprayers

Contents

Page

4.11.2 Travel speed spray robots 11
4.12 Cleaning equipment 12

5 Test methods 12
5.1 Test facilities 12
5.2 Spray and agitation pump(s) 12
5.2.1 Pump capacity test 12
5.2.2 Pump pulsations 14
5.3 Sprayer pressure indicators 14
5.3.1 Specifications of pressure indicators used for verification 14
5.3.2 Verification method of the sprayer pressure indicator 15
5.4 Flow meters for controlling the volume/hectare rate 15
5.4.1 General 15
5.4.2 Operating procedure No.1: Verification by nozzle flow rate measurement 15
5.4.3 Operating procedure No.2: Verification by installing a standard flow meter on the circuit of the sprayer 15
5.5 System for controlling forward speed 15
5.6 Uniformity of the transverse volume distribution with a horizontal patternator 15
5.6.1 Specification of horizontal patternators used for verification 15
5.6.2 Calculation of the coefficient of variation (CV) 16
5.6.3 Verification method of the uniformity of the transverse distribution 16
5.7 Flow rate of the spray nozzles 17
5.7.1 General 17
5.7.2 Measurement with nozzles fitted on the sprayer 17
5.7.3 Measurement with nozzles removed from the sprayer 17
5.8 Pressure drop 17
5.9 Pressure variation when the sections are closed 17
5.10 Pressure variation when the spray is switched off 17
5.11 Accuracy of direct injection systems 18
5.12 Pressure distribution 18

Bibliography 19