ISO 606:2015-08 (E)

Short-pitch transmission precision roller and bush chains, attachments and associated chain sprockets

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Chains 2
3.1 Nomenclature of assemblies and components 2
3.2 Designation 4
3.3 Dimensions 4
3.4 Performance requirements 6
3.4.1 General 6
3.4.2 Tensile testing 7
3.4.3 Preloading 7
3.4.4 Length validation 7
3.4.5 Dynamic testing 7
3.5 Marking 8
3.6 Cranked links 8

4 Attachments 12
4.1 Nomenclature 12
4.2 General 13
4.3 Designation 13
4.4 Dimensions 14
4.5 Manufacture 14
4.6 Marking 14

5 Chain sprockets 16
5.1 General 16
5.2 Nomenclature 16
5.3 Diametral dimensions of sprocket rim 19
5.3.1 Nomenclature 19
5.3.2 Dimensions 19
5.4 Sprocket tooth gap forms 20
5.4.1 Nomenclature 20
5.4.2 Dimensions 20
5.5 Tooth heights and tip diameters 21
5.5.1 Nomenclature 21
5.5.2 Dimensions 21
5.6 Sprocket rim profiles 22
5.6.1 Nomenclature 22
5.6.2 Dimensions 22
5.7 Radial run-out 22
5.8 Axial run-out (wobble) 23
5.9 Pitch accuracy of sprocket teeth 23
5.10 Number of teeth 23
5.11 Bore tolerance 23
5.12 Marking 23

Annex A (normative) Pitch circle diameters 24

Annex B (informative) Equivalent chain designations 26

Annex C (informative) Method of calculating chain minimum dynamic strength 27

Annex D (informative) Method of determining maximum test force Fmax when conducting dynamic strength conformance test 30

Annex E (informative) Examples of methods used to avoid an excessive increase in the rate of stress during the tensile test 31

Annex F (informative) Methods used to approximate the minimum dynamic test values for multiplex chains 34

Bibliography 35