ISO 11031:2016-08 (E)

Cranes - Principles for seismically resistant design

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Symbols 1

4 Seismic design methods 2

5 SeismicdesignbyModifiedSeismicCoefficientMethod 3
5.1 General 3
5.2 Calculation of horizontal seismic design coefficient, KH 3
5.2.1 General 3
5.2.2 Determination of normalized basic acceleration, Abg 3
5.2.3 Determination of subsoil amplification factor, 2 4
5.2.4 Determination of acceleration response factor, 3 5
5.3 Calculation of vertical seismic design coefficient, KV 8
5.4 Calculation of seismic design loads 8
5.4.1 Calculation of seismic accelerations 8
5.4.2 Calculation of seismic forces 9

6 Seismic design based on Maximum Response Spectrum Method 9
6.1 General 9
6.2 Calculation procedure for total seismic response (TSR) 10

7 Combinations of seismic and non-seismic effects 11
7.1 General 11
7.2 Proof of static strength: load combinations in accordance with ISO 8686-1 11
7.3 Proof of static strength: load combination according to SRSS Method 12
7.4 Proof of global stability 12
7.5 Proof of competence for crane structures 13

Annex A (informative) Flow chart of seismic design 14

Annex B (informative) Design accelerations and seismic zones 15

Annex C (informative) Information about Maximum Response Method 32

Annex D (informative) Time History Response Method and a comparison of different seismic methods available 35

Annex E (informative) Relation between basic acceleration, Mercalli and Richter scales 38

Annex F (informative) Vertical seismic intensity 39

Bibliography 40