ISO 6336-5:2016-08 (E)

Calculation of load capacity of spur and helical gears - Part 5: Strength and quality of materials

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms,definitionsandsymbols 2

4 Methodsforthedeterminationofallowablestressnumbers 2
4.1 General 2
4.2 Method A 3
4.3 Method B 3
4.4 Method Br 3
4.5 Method Bk 3
4.6 Method Bp 3

5 Standardallowablestressnumbers--MethodB 3
5.1 Application 3
5.2 Allowable stress number (contact), H lim 4
5.3 Bending stress number values for F lim and FE 5
5.3.1 Nominal stress numbers (bending), F lim 5
5.3.2 Allowable stress number (bending), FE 5
5.3.3 Reversed bending 5
5.4 Graphs for H lim and F lim and FE 6
5.5 Calculation of H lim and F lim 6
5.6 Hardening depth of surface hardened gears in finished condition 23
5.6.1 General 23
5.6.2 Case depth of carburized and hardened gears 23
5.6.3 Nitriding hardening depth of nitrided gears 25

6 Requirements for material quality and heat treatment 26
6.1 General aspects 26
6.2 Normalized low carbon or cast steel, plain carbon, unalloyed steels (see Figures 1 and 2) 27
6.3 Black malleable cast iron [see Figures 3 a) and 4 a)] 27
6.4 Other materials [see Figures 3 b), 3 c), 4 b), 4 c), 5 to 16] 27
6.5 Coupon 40
6.6 Mechanical cleaning by shot blasting 41
6.7 Shot peening 41
6.7.1 General 41
6.7.2 Strength enhancement 41
6.7.3 Salvage 41

Annex A (informative) Considerations of size of controlling section for through hardened gearing 43

AnnexB(informative)Corehardnesscoefficients 46

Bibliography 47