

ISO 6336-5:2016-08 (E)

Calculation of load capacity of spur and helical gears - Part 5: Strength and quality of materials

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms, definitions and symbols	2
4	Methods for the determination of allowable stress numbers	2
4.1	General	2
4.2	Method A	3
4.3	Method B	3
4.4	Method Br	3
4.5	Method Bk	3
4.6	Method Bp	3
5	Standard allowable stress numbers--Method B	3
5.1	Application	3
5.2	Allowable stress number (contact), H lim	4
5.3	Bending stress number values for F lim and FE	5
5.3.1	Nominal stress numbers (bending), F lim	5
5.3.2	Allowable stress number (bending), FE	5
5.3.3	Reversed bending	5
5.4	Graphs for H lim and F lim and FE	6
5.5	Calculation of H lim and F lim	6
5.6	Hardening depth of surface hardened gears in finished condition	23
5.6.1	General	23
5.6.2	Case depth of carburized and hardened gears	23
5.6.3	Nitriding hardening depth of nitrided gears	25
6	Requirements for material quality and heat treatment	26
6.1	General aspects	26
6.2	Normalized low carbon or cast steel, plain carbon, unalloyed steels (see Figures 1 and 2)	27
6.3	Black malleable cast iron [see Figures 3 a) and 4 a)]	27
6.4	Other materials [see Figures 3 b), 3 c), 4 b), 4 c), 5 to 16]	27
6.5	Coupon	40
6.6	Mechanical cleaning by shot blasting	41
6.7	Shot peening	41
6.7.1	General	41
6.7.2	Strength enhancement	41
6.7.3	Salvage	41
Annex A (informative) Considerations of size of controlling section for through hardened gearing ..		43
Annex B (informative) Core hardness coefficients		46
Bibliography		47