

ISO 6336-5:2016-08 (E)

Calculation of load capacity of spur and helical gears - Part 5: Strength and quality of materials

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms, definitions and symbols | 2 |
| 4 | Methods for the determination of allowable stress numbers | 2 |
| 4.1 | General | 2 |
| 4.2 | Method A | 3 |
| 4.3 | Method B | 3 |
| 4.4 | Method Br | 3 |
| 4.5 | Method Bk | 3 |
| 4.6 | Method Bp | 3 |
| 5 | Standard allowable stress numbers--Method B | 3 |
| 5.1 | Application | 3 |
| 5.2 | Allowable stress number (contact), H lim | 4 |
| 5.3 | Bending stress number values for F lim and FE | 5 |
| 5.3.1 | Nominal stress numbers (bending), F lim | 5 |
| 5.3.2 | Allowable stress number (bending), FE | 5 |
| 5.3.3 | Reversed bending | 5 |
| 5.4 | Graphs for H lim and F lim and FE | 6 |
| 5.5 | Calculation of H lim and F lim | 6 |
| 5.6 | Hardening depth of surface hardened gears in finished condition | 23 |
| 5.6.1 | General | 23 |
| 5.6.2 | Case depth of carburized and hardened gears | 23 |
| 5.6.3 | Nitriding hardening depth of nitrided gears | 25 |
| 6 | Requirements for material quality and heat treatment | 26 |
| 6.1 | General aspects | 26 |
| 6.2 | Normalized low carbon or cast steel, plain carbon, unalloyed steels (see Figures 1 and 2) | 27 |
| 6.3 | Black malleable cast iron [see Figures 3 a) and 4 a)] | 27 |
| 6.4 | Other materials [see Figures 3 b), 3 c), 4 b), 4 c), 5 to 16] | 27 |
| 6.5 | Coupon | 40 |
| 6.6 | Mechanical cleaning by shot blasting | 41 |
| 6.7 | Shot peening | 41 |
| 6.7.1 | General | 41 |
| 6.7.2 | Strength enhancement | 41 |
| 6.7.3 | Salvage | 41 |
| Annex A (informative) Considerations of size of controlling section for through hardened gearing .. | | 43 |
| Annex B (informative) Core hardness coefficients | | 46 |
| Bibliography | | 47 |