

ISO 18063-1:2016-11 (E)

Rough-terrain trucks - Visibility - Test methods and their verification - Part 1: Variable-reach trucks

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Test apparatus	5
4.1	Light source apparatus	5
4.2	Vertical test object	5
4.3	Observation mirror	5
5	Truck test configuration	5
5.1	Equipment of the truck	5
5.2	Openings	6
5.3	Position of the truck and load handling attachment	6
6	Measurement procedure	6
6.1	Test-surface marking and truck location on the test surface	6
6.2	Positioning of the test apparatus	7
6.3	Measurements of the maskings	8
6.3.1	General	8
6.3.2	Measurement at the visibility test circle	8
6.3.3	Measurement at the rectangular 1 m boundary	9
6.4	Requirements for derivative trucks	10
7	Evaluation method and performance criteria	10
7.1	Visibility performance criteria on the visibility test circle	10
7.2	Visibility performance criteria for the rectangular 1 m boundary	10
7.3	Visibility maskings that exceed the visibility performance criteria with direct view	10
8	Calculation method and computer simulation	10
9	Test report	10
9.1	Truck details	10
9.2	Drawing	11
10	Information for use	11
Annex A (informative) Light source spacing dimensions		13
Annex B (informative) Performance criteria for additional devices		14
Annex C (informative) Procedure for the determination of maskings at the visibility test circle or the rectangular 1 m boundary		15
Annex D (informative) Examples of drawings for the test report		16
Bibliography		17