

# ISO 4548-3:1997-09 (E)

## Methods of test for full-flow lubricating oil filters for internal combustion engines - Part 3: Resistance to high differential pressure and to elevated temperature

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Definitions .....</b>	<b>1</b>
<b>4</b>	<b>Graphical symbols .....</b>	<b>1</b>
<b>5</b>	<b>Operational characteristics to be tested .....</b>	<b>1</b>
<b>6</b>	<b>Filter to be tested .....</b>	<b>1</b>
<b>6.1</b>	<b>Filter type .....</b>	<b>2</b>
<b>6.2</b>	<b>Filter element .....</b>	<b>2</b>
<b>7</b>	<b>Testrig .....</b>	<b>2</b>
<b>7.1</b>	<b>Sump .....</b>	<b>2</b>
<b>7.2</b>	<b>Regulating valves .....</b>	<b>2</b>
<b>7.3</b>	<b>Flow meter .....</b>	<b>2</b>
<b>7.4</b>	<b>Filter mounting .....</b>	<b>2</b>
<b>8</b>	<b>Test liquids .....</b>	<b>6</b>
<b>8.1</b>	<b>Test liquids for test of ability to withstand high differential pressure .....</b>	<b>6</b>
<b>8.2</b>	<b>Test liquid for test of ability to withstand elevated temperature .....</b>	<b>6</b>
<b>9</b>	<b>Accuracy of test condition measurements .....</b>	<b>6</b>
<b>10</b>	<b>Test procedure .....</b>	<b>6</b>
<b>10.1</b>	<b>Test for ability to withstand high differential pressure .....</b>	<b>6</b>
<b>10.2</b>	<b>Test for ability to withstand elevated temperature .....</b>	<b>7</b>
<b>11</b>	<b>Report of test results .....</b>	<b>7</b>
<b>11.1</b>	<b>High differential pressure test .....</b>	<b>7</b>
<b>11.2</b>	<b>Elevated temperature test .....</b>	<b>8</b>
	<b>Annex A (informative) Bibliography .....</b>	<b>9</b>

