

DIN EN 16842-2:2018-10 (E)

Powered industrial trucks - Visibility - Test methods and verification - Part 2: Sit-on counterbalance trucks and rough terrain masted trucks up to and including 10 000 kg capacity

Contents		Page
European foreword		3
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	Truck configuration	6
4.1	General	6
4.2	Fork arm dimensions	6
5	Test equipment	7
6	Test procedures for direct visibility	7
6.1	Lighting equipment position	7
6.2	Test paths for trucks < 10 000 kg	8
6.3	Measurement procedure	9
6.4	Test procedure for indirect visibility	9
7	Acceptance criteria	9
7.1	General	9
7.2	Direct visibility	9
7.2.1	General	9
7.2.2	Travelling visibility	9
7.2.3	Manoeuvring visibility	9
7.2.4	Fork arms	9
7.3	Indirect visibility	9
7.4	Criteria for trucks up to and including 5 000 kg rated capacity	10
7.5	Trucks greater than 5 000 kg and up to and including 10 000 kg rated capacity	11
8	Test report	12
9	Information for use	12
Annex A (informative) Information for operator visibility during use		13
A.1	General	13
A.2	Method 1	14
A.3	Method 2	15
Bibliography		16