

DIN EN ISO 5801:2018-04 (E)

Fans - Performance testing using standardized airways (ISO 5801:2017)

Contents

| | Page |
|---|-----------|
| European foreword | 6 |
| Foreword | 7 |
| Introduction | 8 |
| 1 Scope | 9 |
| 2 Normative references | 9 |
| 3 Terms and definitions | 9 |
| 4 Symbols, abbreviated terms and subscripts | 18 |
| 4.1 Symbols and abbreviated terms | 18 |
| 4.2 Subscripts | 20 |
| 5 General | 21 |
| 6 Test configurations | 22 |
| 6.1 General | 22 |
| 6.2 Category A configuration | 23 |
| 6.3 Category B configuration | 23 |
| 6.4 Category C configuration | 23 |
| 6.5 Category D configuration | 23 |
| 6.6 Inlets and outlets | 23 |
| 6.7 Fans with significant swirl | 23 |
| 6.8 Airways | 23 |
| 6.9 Test space | 24 |
| 6.10 Leakage | 24 |
| 6.11 Test report | 24 |
| 7 Carrying out the test | 24 |
| 7.1 Working fluid | 24 |
| 7.2 Rotational speed | 24 |
| 7.3 Steady operation | 24 |
| 7.4 Ambient conditions | 24 |
| 7.5 Pressure readings | 25 |
| 7.6 Test for a specified duty | 25 |
| 7.7 Test for a fan characteristic curve | 25 |
| 7.8 Operating range | 25 |
| 8 Airways for duct simulations | 25 |
| 8.1 General | 25 |
| 8.2 Common segments at fan inlet (iCS) | 25 |
| 8.3 Inlet duct simulation (iDS) | 27 |
| 8.4 Common segment at fan outlet (oCS) | 28 |
| 8.5 Outlet duct simulation (oDS) | 29 |
| 8.6 Long duct (LD) | 30 |
| 8.7 Loss allowances for standardized airways | 31 |
| 8.7.1 Loss allowances for an inlet common segment (iCS) | 31 |
| 8.7.2 Loss allowances for inlet duct simulation (iDS) | 32 |
| 8.7.3 Loss allowances for outlet common segments (oCS) | 32 |
| 8.7.4 Loss allowances for duct simulation at outlet (oDS) | 33 |
| 8.7.5 Loss allowances for long duct (LD) | 33 |
| 9 Standardized test chambers | 33 |
| 9.1 General | 33 |
| 9.2 Pressure tappings | 33 |

| | | |
|-----------|---|-----------|
| 9.3 | Flow-settling means | 33 |
| 9.3.1 | General..... | 33 |
| 9.3.2 | Piezometer ring check..... | 34 |
| 9.3.3 | Blow through verification test | 34 |
| 9.3.4 | Outlet chamber reverse flow verification test..... | 34 |
| 9.4 | Standardized inlet test chambers (iTc)..... | 34 |
| 9.4.1 | Test chambers | 34 |
| 9.4.2 | Fan under test..... | 37 |
| 9.5 | Standardized outlet test chambers (oTc)..... | 38 |
| 9.5.1 | Test chambers | 38 |
| 9.5.2 | Fan under test..... | 38 |
| 10 | Various component parts for a laboratory setup | 39 |
| 10.1 | General..... | 39 |
| 10.2 | Variable supply system | 39 |
| 10.2.1 | General..... | 39 |
| 10.2.2 | Throttling device..... | 39 |
| 10.2.3 | Auxiliary fan..... | 39 |
| 10.3 | Straightener | 39 |
| 10.3.1 | General..... | 39 |
| 10.3.2 | Cell straightener | 39 |
| 10.3.3 | Star straightener | 40 |
| 10.4 | Transition parts..... | 41 |
| 10.4.1 | General..... | 41 |
| 10.4.2 | Rectangular/circular transition | 42 |
| 10.4.3 | Circular/circular transition | 42 |
| 10.4.4 | Connection for double-inlet fans | 43 |
| 11 | Standard test configurations | 43 |
| 11.1 | Units | 43 |
| 11.2 | Measuring flow rate..... | 48 |
| 11.3 | Standard test configurations A | 49 |
| 11.4 | Standard test configurations B | 50 |
| 11.5 | Standard test configurations C | 50 |
| 11.6 | Standard test configurations D | 50 |
| 12 | Measurements | 51 |
| 12.1 | Calibration | 51 |
| 12.2 | Dimensions and cross-sectional areas | 51 |
| 12.2.1 | Tolerance on dimensions | 51 |
| 12.2.2 | Cross-sectional area | 51 |
| 12.3 | Rotational speed | 52 |
| 12.4 | Power input | 52 |
| 12.4.1 | General..... | 25 |
| 12.4.2 | Motor input power | 52 |
| 12.4.3 | Fan shaft power | 53 |
| 12.4.4 | Impeller power | 54 |
| 12.4.5 | Transmission systems | 54 |
| 12.5 | Mass flow rate | 54 |
| 12.6 | Temperature | 55 |
| 12.6.1 | General..... | 55 |
| 12.6.2 | Accuracy of temperature measurement | 55 |
| 12.6.3 | Correction for high velocities | 55 |
| 12.7 | Humidity | 56 |
| 12.8 | Pressure | 56 |
| 12.8.1 | Barometers | 56 |
| 12.8.2 | Manometers | 57 |
| 12.8.3 | Damping of manometers | 57 |
| 12.8.4 | Checking of manometers | 57 |
| 12.8.5 | Position of manometers | 57 |
| 12.8.6 | Average pressure in an airway | 58 |
| 12.8.7 | Construction of tappings | 58 |
| 12.8.8 | Position and connections | 59 |
| 12.8.9 | Methods of measurement | 59 |
| 12.8.10 | Checks for compliance | 59 |

| | | |
|---|---|-----------|
| 12.8.11 | Use of Pitot-static tube..... | 59 |
| 12.9 | Air properties..... | 60 |
| 12.9.1 | General..... | 60 |
| 12.9.2 | Density of air at section x | 60 |
| 12.9.3 | Air viscosity..... | 61 |
| 12.9.4 | Standard air..... | 61 |
| 13 | Reference conditions | 61 |
| 14 | General rules for conversion of test results | 62 |
| 14.1 | General..... | 62 |
| 14.2 | Laws on fan similarity..... | 62 |
| 14.2.1 | General..... | 62 |
| 14.2.2 | Geometrical similarity..... | 62 |
| 14.2.3 | Reynolds number similarity..... | 63 |
| 14.2.4 | Mach number and similarity of the velocity triangles..... | 63 |
| 15 | Calculations..... | 63 |
| 15.1 | Test results..... | 63 |
| 15.1.1 | General..... | 63 |
| 15.1.2 | Temperature | 64 |
| 15.1.3 | Pressure | 66 |
| 15.1.4 | Set of formulae..... | 66 |
| 15.1.5 | Simplified sets of formulae, which can be used for $v_{2,\text{ref}} \leq 65\text{m/s}$ | 68 |
| 15.1.6 | Fan pressure | 69 |
| 15.1.7 | Fan static pressure | 70 |
| 15.1.8 | Volume flow rate of the fan | 70 |
| 15.1.9 | Fan air power and efficiency | 70 |
| 15.2 | Efficiencies..... | 73 |
| 15.2.1 | General..... | 73 |
| 15.2.2 | Fan static air power and static efficiency | 74 |
| 15.3 | Conversion rules..... | 74 |
| 15.3.1 | General..... | 74 |
| 15.3.2 | Shaft power and impeller power | 74 |
| 16 | Fan characteristic curves | 75 |
| 16.1 | Methods of plotting..... | 75 |
| 16.2 | Characteristic curves at constant speed..... | 75 |
| 16.3 | Characteristic curves at inherent speed..... | 76 |
| 16.4 | Complete fan characteristic curve | 76 |
| 16.5 | Test for a specified duty | 77 |
| 16.6 | Specific fan types..... | 77 |
| 17 | Uncertainty analysis | 78 |
| 17.1 | Principle | 78 |
| 17.2 | Pre-test and post-test analysis | 78 |
| 17.3 | Analysis procedure | 78 |
| 17.4 | Propagation of uncertainties | 78 |
| 17.5 | Reporting uncertainties | 79 |
| 17.6 | Maximum allowable uncertainties for measurements | 79 |
| 17.7 | Maximum allowable uncertainty of results | 80 |
| Annex A (normative) Determination of air flow rate | 81 | |
| Annex B (informative) Fan-powered roof exhaust ventilators | 98 | |
| Annex C (informative) Chamber leakage test procedure | 99 | |
| Annex D (informative) Fan outlet elbow in the case of a non-horizontal discharge axis | 105 | |
| Annex E (informative) Input power calculation for driven fans at design point | 108 | |
| Annex F (informative) Motor fed from a variable frequency speed device | 117 | |

| | |
|--|------------|
| Annex G (informative) Axial fans without outlet guide vanes..... | 118 |
| Annex H (informative) Vapour pressure, p_v | 120 |
| Annex I (informative) Clearances | 121 |
| Annex J (normative) Polytropic approach for the calculation of p_{fc} from p_{fTe} | 123 |
| Annex K (informative) Examples for test setups..... | 125 |
| Annex L (informative) Measurement of plenum fans and plug fans..... | 133 |
| Annex M (informative) Comparison of NEMA methodology for calculation motor efficiency with IEC..... | 135 |
| Annex N (informative) Report and results of test..... | 136 |
| Bibliography | 144 |