

# DIN 28430:2017-06 (E)

## Vacuum technology - Rules for the measurement of steam jet vacuum pumps and steam jet compressors - Motive fluid: steam

---

| <b>Contents</b>           |  | <b>Page</b> |
|---------------------------|--|-------------|
| Foreword .....            |  | 3           |
| <b>1</b>                  | <b>Scope .....</b>   | <b>4</b>    |
| <b>2</b>                  | <b>Normative references .....</b>  | <b>4</b>    |
| <b>3</b>                  | <b>Terms and definitions .....</b>   | <b>4</b>    |
| <b>4</b>                  | <b>Symbols and abbreviations .....</b>   | <b>6</b>    |
| <b>5</b>                  | <b>Specified performance data .....</b>  | <b>7</b>    |
| <b>6</b>                  | <b>Principles of measurement and calculation .....</b>   | <b>7</b>    |
| <b>6.1</b>                | <b>Equivalent suction flows of single-stage and multi-stage steam jet vacuum pumps without intercondensers .....</b> | <b>7</b>    |
| <b>6.2</b>                | <b>Suction flows for multi-stage steam jet vacuum pumps with intercondensers .....</b>                               | <b>8</b>    |
| <b>6.3</b>                | <b>Determination of mass flow rates .....</b>  | <b>9</b>    |
| <b>6.3.1</b>              | <b>General .....</b>   | <b>9</b>    |
| <b>6.3.2</b>              | <b>Determination of the suction flow rate .....</b>  | <b>10</b>   |
| <b>6.3.3</b>              | <b>Determination of the motive steam flow rate .....</b>   | <b>13</b>   |
| <b>6.3.4</b>              | <b>Suction temperature .....</b>   | <b>14</b>   |
| <b>6.3.5</b>              | <b>Motive steam temperature .....</b>  | <b>14</b>   |
| <b>6.4</b>                | <b>Measurement uncertainties .....</b>   | <b>14</b>   |
| <b>7</b>                  | <b>Carrying out and evaluating the tests .....</b>   | <b>14</b>   |
| <b>7.1</b>                | <b>Preparation .....</b>   | <b>14</b>   |
| <b>7.2</b>                | <b>Conditions during measurement .....</b>   | <b>15</b>   |
| <b>7.2.1</b>              | <b>Carrying out the measurements .....</b>   | <b>15</b>   |
| <b>7.2.2</b>              | <b>Suction flow rate .....</b>   | <b>15</b>   |
| <b>7.2.3</b>              | <b>Suction pressure .....</b>  | <b>15</b>   |
| <b>7.2.4</b>              | <b>Limiting back pressure .....</b>  | <b>15</b>   |
| <b>7.3</b>                | <b>Evaluation of measurements .....</b>  | <b>15</b>   |
| <b>7.4</b>                | <b>Testing under conditions deviating from the design values .....</b>   | <b>16</b>   |
| <b>7.4.1</b>              | <b>General .....</b>   | <b>16</b>   |
| <b>7.4.2</b>              | <b>Absence of sufficiently superheated motive steam .....</b>  | <b>16</b>   |
| <b>7.4.3</b>              | <b>Absence of sufficient mass flow rates or motive steam pressures .....</b>   | <b>16</b>   |
| <b>7.4.4</b>              | <b>Absence of sufficiently high back pressure .....</b>  | <b>17</b>   |
| <b>Bibliography .....</b> |  | <b>18</b>   |