

# ISO 5006:2017-04 (E)

## Earth-moving machinery - Operator's field of view - Test method and performance criteria

---

| <b>Contents</b>    |  | <b>Page</b> |
|--------------------|--|-------------|
| Foreword .....     |  | iv          |
| Introduction ..... |  | v           |
| 1                  | Scope .....  | 1           |
| 2                  | Normative references .....   | 1           |
| 3                  | Terms and definitions .....  | 1           |
| 4                  | Basic dimensions .....   | 5           |
| 4.1                | Light spacing dimensions .....   | 5           |
| 4.2                | Masking dimensions .....   | 5           |
| 4.3                | Reference dimensions for measurement purposes .....  | 5           |
| 5                  | Test apparatus .....   | 5           |
| 6                  | Machine test configuration .....   | 6           |
| 7                  | Performance criteria for indirect visibility .....   | 6           |
| 7.1                | Visibility aids .....  | 6           |
| 7.2                | Position of display devices .....  | 6           |
| 7.3                | Performance criteria for mirrors .....   | 6           |
| 7.4                | Performance criteria for CCTV system .....   | 7           |
| 8                  | Measurement procedure .....  | 7           |
| 8.1                | Test-surface marking and machine location on test surface .....  | 7           |
| 8.2                | Positioning of test apparatus .....  | 7           |
| 8.3                | Measurement of maskings .....  | 8           |
| 8.3.1              | General .....  | 8           |
| 8.3.2              | Measurement at the VTC .....   | 9           |
| 8.3.3              | Measurement at RB .....  | 9           |
| 9                  | Calculation method .....   | 11          |
| 9.1                | Calculation procedure for determining maskings at VTC or RB .....  | 11          |
| 9.2                | Computer-simulation .....  | 12          |
| 10                 | Evaluation method and performance criteria .....   | 12          |
| 10.1               | Visibility performance criteria on VTC .....   | 12          |
| 10.2               | Visibility performance criteria for RB .....   | 17          |
| 10.3               | Visibility maskings that exceed visibility performance criteria with direct view .....   | 18          |
| 10.4               | Requirements for larger, derivative and other types of earth-moving machinery not covered in Table 1 and Table 2 .....           | 19          |
| 10.4.1             | Larger machines .....  | 19          |
| 10.4.2             | Derivative and other types of earth-moving machinery .....   | 20          |
| 10.4.3             | Risk assessment process for larger, derivative or other types of earth-moving machinery not covered in Table 1 and Table 2 ..... | 20          |
| 10.4.4             | Visibility test circle and allowed masking width .....   | 20          |
| 11                 | Test report .....  | 20          |
| 11.1               | Machine details .....  | 20          |

|                     |   |    |
|---------------------|---|----|
| 11.2                | Drawing .....   | 21 |
| 12                  | Visibility information for operator's manual .....                | 21 |
| Annex A (normative) | Dimensions and position of HH and rectangular boundary (RB) ..... | 22 |
| Bibliography .....  |   | 29 |