

ISO 5682-2:2017-05 (E)

Equipment for crop protection - Spraying equipment - Part 2: Test methods to assess the horizontal transverse distribution for hydraulic sprayers

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Measuring equipment	1
5	Test conditions	2
5.1	General	2
5.2	Temperature and relative humidity	2
5.3	Choice of nozzles for the tests	2
5.4	Control pressure	2
6	Test methods	2
6.1	General	2
6.2	Standard conditions	3
6.3	Transverse distribution evaluation by means of sprayed liquid volume measurement - sprayed liquid volume measurement method	3
6.3.1	Setup	3
6.3.2	Measurement	3
6.3.3	Results	4
6.4	Nozzle tip position	4
6.4.1	Spacing	4
6.4.2	Alignment	4
6.5	Transverse distribution evaluation by means of nozzle flow rate measurement - nozzle flow rate measurement test method	4
6.5.1	Setup	4
6.5.2	Measurements	5
6.5.3	Results	5
6.6	Transverse distribution evaluation by means of nozzle tip pressure measurement - nozzle tip pressure measurement test method	5
6.6.1	Setup	5
6.6.2	Measurements	6
6.6.3	Results	6
Annex A (informative) Transverse distribution test report		7
Annex B (informative) Applicable test methods		9
Annex C (informative) Guidance to estimate horizontal transverse distribution		10