

# ISO 5682-2:2017-05 (E)

## Equipment for crop protection - Spraying equipment - Part 2: Test methods to assess the horizontal transverse distribution for hydraulic sprayers

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Measuring equipment .....</b>	<b>1</b>
<b>5</b>	<b>Test conditions .....</b>	<b>2</b>
5.1	General .....	2
5.2	Temperature and relative humidity .....	2
5.3	Choice of nozzles for the tests .....	2
5.4	Control pressure .....	2
<b>6</b>	<b>Test methods .....</b>	<b>2</b>
6.1	General .....	2
6.2	Standard conditions .....	3
6.3	Transverse distribution evaluation by means of sprayed liquid volume measurement - sprayed liquid volume measurement method .....	3
6.3.1	Setup .....	3
6.3.2	Measurement .....	3
6.3.3	Results .....	4
6.4	Nozzle tip position .....	4
6.4.1	Spacing .....	4
6.4.2	Alignment .....	4
6.5	Transverse distribution evaluation by means of nozzle flow rate measurement - nozzle flow rate measurement test method .....	4
6.5.1	Setup .....	4
6.5.2	Measurements .....	5
6.5.3	Results .....	5
6.6	Transverse distribution evaluation by means of nozzle tip pressure measurement - nozzle tip pressure measurement test method .....	5
6.6.1	Setup .....	5
6.6.2	Measurements .....	6
6.6.3	Results .....	6
<b>Annex A (informative) Transverse distribution test report .....</b>		<b>7</b>
<b>Annex B (informative) Applicable test methods .....</b>		<b>9</b>
<b>Annex C (informative) Guidance to estimate horizontal transverse distribution .....</b>		<b>10</b>