

ISO 4548-12:2017-05 (E)

Methods of test for full-flow lubricating oil filters for internal combustion engines - Part 12: Filtration efficiency using particle counting and contaminant retention capacity

| Contents | | Page |
|----------------------------|--------------------------------------------------------------------|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols | 2 |
| 5 | Test equipment and materials | 2 |
| 5.1 | Test equipment | 2 |
| 5.1.1 | Test rig | 2 |
| 5.1.2 | Online dilution and particle counting system | 4 |
| 5.1.3 | Timer | 5 |
| 5.2 | Test materials | 5 |
| 5.2.1 | Test contaminant | 5 |
| 5.2.2 | Test fluid | 5 |
| 6 | Accuracy of measuring instruments and test conditions | 5 |
| 7 | Test rig validation | 6 |
| 7.1 | Validation of filter test circuit | 6 |
| 7.2 | Validation of contaminant injection circuit | 6 |
| 7.3 | Validation of online dilution and particle counting system | 7 |
| 8 | Preliminary preparation | 7 |
| 8.1 | Test filter assembly | 7 |
| 8.2 | Contaminant injection circuit | 7 |
| 8.3 | Filter test circuit | 9 |
| 9 | Test procedure | 9 |
| 9.1 | Initial measurement | 9 |
| 9.2 | Performance test | 11 |
| 10 | Calculations and report of test results | 12 |
| 10.1 | Calculations | 12 |
| 10.1.1 | General | 12 |
| 10.1.2 | Gravimetric levels | 12 |
| 10.1.3 | Filtration efficiencies | 13 |
| 10.1.4 | Micrometer ratings | 13 |
| 10.1.5 | Injected mass of contaminant | 14 |
| 10.1.6 | Non-retained mass of contaminant | 14 |
| 10.1.7 | Retained filter capacity | 14 |
| 10.2 | Test report | 14 |
| Annex A (normative) | Specification of test fluid for oil filter test | 15 |

| | |
|-----------------------------------------------------------------|-----------|
| Annex B (informative) Typical filter test report | 16 |
| Annex C (normative) Filter efficiency calculations | 22 |
| Annex D (informative) Round robin exercise | 25 |
| Bibliography | 32 |