

ISO 3968:2017-07 (E)

Hydraulic fluid power - Filters - Evaluation of differential pressure versus flow

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols	2
4.1	Letter symbols	2
4.2	Graphical symbols	2
5	Operational characteristics to be tested	2
6	Filter to be tested	3
6.1	Filter type	3
6.2	Filter element	3
7	Test equipment	3
7.1	General indications	3
7.2	Pump	3
7.3	Reservoir	3
7.4	Temperature control	4
7.5	Clean-up filter	4
7.6	Sampling valve	4
7.7	Mounting of filter	5
7.8	Test fluid	6
8	Measurements	6
8.1	Pressure measurement	6
8.2	Temperature measurement	8
8.3	Kinematic viscosity measurement	8
8.4	Flow rate measurement	9
8.5	Fluid cleanliness measurement	9
8.6	Accuracy of measuring instruments and test conditions	9
9	Procedure	9
9.1	Pipework correction	9
9.2	Cleanliness of test circuit	9
9.3	Characteristics of the filter housing (filter type 6.1.3)	10
9.4	Characteristics of the filter assembly (filter type 6.1.3)	10
9.5	Characteristics of the filter element only (filter type 6.1.3)	10
9.6	Characteristics of the head and spin-on (filter type 6.1.2)	10
9.7	Characteristics of the spin-on (filter type 6.1.1)	11
9.8	Characteristics of the bypass valve	11
9.8.1	Preliminary installation	11
9.8.2	Determination of full flow rate characteristics	11
9.8.3	Determination of opening pressure	11
9.8.4	Determination of closing pressure	12
9.8.5	Measurement of leakage rate	12

10	Presentation of results	12
11	Identification statement (reference to this document)	14
	Annex A (informative) Introduction to the power loss equation and method to calculate	15
	Bibliography	17