

ISO/TR 6336-30:2017-11 (E)

Calculation of load capacity of spur and helical gears - Part 30: Calculation examples for the application of ISO 6336 parts 1,2,3,5

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and units	1
3.1	Terms and definitions	1
3.2	Symbols and units	2
4	Worked examples	5
4.1	General	5
4.2	Qualifying comments	6
4.2.1	Calculation of base pitch deviation, f_{pb}, and its application to the running in allowances ..	6
4.2.2	Calculation of mesh stiffness, c	6
4.2.3	Application of lubricant film Z_L, Z_v and Z_R, hardness Z_W and size Z_X influence factors	6
4.2.4	Application of work hardening factor, Z_W	6
4.2.5	Determination of R_z	6
4.2.6	Face width for calculations involving double helical gears	6
4.2.7	Calculation of σ_H for double helical gears	6
4.2.8	Calculation of f_{H5} and f_H	7
4.2.9	Helix tolerance f_{H5} and f_H for double helical gears	7
4.2.10	Calculation of root diameter, d_f	7
4.2.11	Amendment to ISO 6336-3:2006, Formula (10) auxiliary value, E	7
4.2.12	Calculations for internal gears	7
4.3	Example 1: Single helical case carburized gear pair	8
4.4	Example 2: Single helical through-hardened gear pair	12
4.5	Example 3: Spur through-hardened gear pair	16
4.6	Example 4: Spur case carburized gear pair	20
4.7	Example 5: Spur gear pair with an induction hardened pinion and through-hardened cast gear	24
4.8	Example 6: Spur internal through-hardened gear pair	28
4.9	Example 7: Double helical through-hardened gear pair	32
4.10	Example 8: Single helical case carburized gear pair	36
Annex A (informative)	Example 1 detailed calculation	40
Bibliography		60