ISO/TS 6336-21:2017-11 (E)

Calculation of load capacity of spur and helical gears - Part 21: Calculation of scuffing load capacity (also applicable to bevel and hypoid gears) - Integral temperature method

Contents

Page

Foreword ... **v**

Introduction ... **vi**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms, definitions, symbols and units ... **1**
3.1 Terms and definitions ... 1
3.2 Symbols and units ... 1

4 Field of application ... **6**
4.1 General ... 6
4.2 Scuffing damage ... 6
4.3 Integral temperature criterion ... 6

5 Influence factors ... **6**
5.1 Mean coefficient of friction, μ_{mC} ... 6
5.2 Run-in factor, X_E ... 9
5.3 Thermal flash factor, X_M ... 10
5.4 Pressure angle factor, $X_{\alpha\beta}$ ... *11*

6 Calculation ... **12**
6.1 Cylindrical gears ... 12
6.1.1 General ... 12
6.1.2 Scuffing safety factor, S_{intS} ... 12
6.1.3 Permissible integral temperature, ϑ_{intP} ... 12
6.1.4 Integral temperature, ϑ_{int} ... 13
6.1.5 Flash temperature at pinion tooth tip, ϑ_{flaE} ... 13
6.1.6 Bulk temperature, ϑ_M ... 13
6.1.7 Mean coefficient of friction, μ_{mC} ... 14
6.1.8 Run-in factor, X_E ... 14
6.1.9 Thermal flash factor, X_M ... 14
6.1.10 Pressure angle factor, $X_{\alpha\beta}$ ... *14*
6.1.11 Geometry factor at tip of pinion, X_{BE} ... 14
6.1.12 Approach factor, X_Q ... 15
6.1.13 Tip relief factor, X_{Ca} ... 16
6.1.14 Contact ratio factor, X_ε ... *17*
6.2 Bevel gears ... 19
6.2.1 General ... 19
6.2.2 Scuffing safety factor, S_{intS} ... 20
6.2.3 Permissible integral temperature , ϑ_{intP} ... 20
6.2.4 Permissible integral temperature, ϑ_{intP} ... 20
6.2.5 Flash temperature at pinion tooth tip, ϑ_{flaE} ... 20
6.2.6 Bulk temperature, ϑ_M ... 20
6.2.7 Mean coefficient of friction, μ_{mC} ... 20
6.2.8 Run-in factor, X_E ... 20
6.2.9 Thermal flash factor, X_M ... 21
6.2.10 Pressure angle factor, $X_{\alpha\beta}$ ... *21*
6.2.11 Geometry factor at tip of pinion, X_{BE} ... 21
6.2.12 Approach factor, X_Q ... 21
6.2.13 Tip relief factor, X_{Ca} ... 21
6.2.14 Contact ratio factor, X_ε ... 22

6.3 Hypoid gears 22
6.3.1 General 22
6.3.2 Scuffing safety factor, S_{intS} 22
6.3.3 Permissible integral temperature, ϑ_{intP} 22
6.3.4 Integral temperature, ϑ_{nt} 22
6.3.5 Bulk temperature, ϑ_{M} 22
6.3.6 Mean coefficient of friction, μ_{mC} 23
6.3.7 Run-in factor, X_{E} 23
6.3.8 Geometry factor, X_{G} 23
6.3.9 Approach factor, X_{Q} 25
6.3.10 Tip relief factor, X_{Ca} 25
6.3.11 Contact ratio factor, X_{ε} 25
6.3.12 Calculation of virtual crossed axes helical gears 25
6.4 Scuffing integral temperature 29
6.4.1 General 29
6.4.2 Scuffing integral temperature, ϑ_{intS} 29
6.4.3 Relative welding factor, X_{WrelT} 34
Annex A (informative) **Examples** **35**
Annex B (informative) **Contact-time-dependent scuffing temperature** **44**
Bibliography **49**