

# ISO/TS 6336-21:2017-11 (E)

## Calculation of load capacity of spur and helical gears - Part 21: Calculation of scuffing load capacity (also applicable to bevel and hypoid gears) - Integral temperature method

<b>Contents</b>		<b>Page</b>
	Foreword.....	v
	Introduction.....	vi
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Normative references</b> .....	<b>1</b>
<b>3</b>	<b>Terms, definitions, symbols and units</b> .....	<b>1</b>
	3.1 Terms and definitions.....	1
	3.2 Symbols and units.....	1
<b>4</b>	<b>Field of application</b> .....	<b>6</b>
	4.1 General.....	6
	4.2 Scuffing damage.....	6
	4.3 Integral temperature criterion.....	6
<b>5</b>	<b>Influence factors</b> .....	<b>6</b>
	5.1 Mean coefficient of friction, $\mu_{mC}$ .....	6
	5.2 Run-in factor, $X_E$ .....	9
	5.3 Thermal flash factor, $X_M$ .....	10
	5.4 Pressure angle factor, $X_{\alpha\beta}$ .....	11
<b>6</b>	<b>Calculation</b> .....	<b>12</b>
	6.1 Cylindrical gears.....	12
	6.1.1 General.....	12
	6.1.2 Scuffing safety factor, $S_{intS}$ .....	12
	6.1.3 Permissible integral temperature, $\vartheta_{intP}$ .....	12
	6.1.4 Integral temperature, $\vartheta_{int}$ .....	13
	6.1.5 Flash temperature at pinion tooth tip, $\vartheta_{flaE}$ .....	13
	6.1.6 Bulk temperature, $\vartheta_M$ .....	13
	6.1.7 Mean coefficient of friction, $\mu_{mC}$ .....	14
	6.1.8 Run-in factor, $X_E$ .....	14
	6.1.9 Thermal flash factor, $X_M$ .....	14
	6.1.10 Pressure angle factor, $X_{\alpha\beta}$ .....	14
	6.1.11 Geometry factor at tip of pinion, $X_{BE}$ .....	14
	6.1.12 Approach factor, $X_Q$ .....	15
	6.1.13 Tip relief factor, $X_{Ca}$ .....	16
	6.1.14 Contact ratio factor, $X_\epsilon$ .....	17
	6.2 Bevel gears.....	19
	6.2.1 General.....	19
	6.2.2 Scuffing safety factor, $S_{intS}$ .....	20
	6.2.3 Permissible integral temperature, $\vartheta_{intP}$ .....	20
	6.2.4 Permissible integral temperature, $\vartheta_{intP}$ .....	20
	6.2.5 Flash temperature at pinion tooth tip, $\vartheta_{flaE}$ .....	20
	6.2.6 Bulk temperature, $\vartheta_M$ .....	20
	6.2.7 Mean coefficient of friction, $\mu_{mC}$ .....	20
	6.2.8 Run-in factor, $X_E$ .....	20
	6.2.9 Thermal flash factor, $X_M$ .....	21
	6.2.10 Pressure angle factor, $X_{\alpha\beta}$ .....	21
	6.2.11 Geometry factor at tip of pinion, $X_{BE}$ .....	21
	6.2.12 Approach factor, $X_Q$ .....	21
	6.2.13 Tip relief factor, $X_{Ca}$ .....	21
	6.2.14 Contact ratio factor, $X_\epsilon$ .....	22

6.3	Hypoid gears .....	22
6.3.1	General.....	22
6.3.2	Scuffing safety factor, $S_{\text{ints}}$ .....	22
6.3.3	Permissible integral temperature, $\vartheta_{\text{intP}}$ .....	22
6.3.4	Integral temperature, $\vartheta_{\text{nt}}$ .....	22
6.3.5	Bulk temperature, $\vartheta_{\text{M}}$ .....	22
6.3.6	Mean coefficient of friction, $\mu_{\text{mC}}$ .....	23
6.3.7	Run-in factor, $X_{\text{E}}$ .....	23
6.3.8	Geometry factor, $X_{\text{G}}$ .....	23
6.3.9	Approach factor, $X_{\text{Q}}$ .....	25
6.3.10	Tip relief factor, $X_{\text{Ca}}$ .....	25
6.3.11	Contact ratio factor, $X_{\text{c}}$ .....	25
6.3.12	Calculation of virtual crossed axes helical gears .....	25
6.4	Scuffing integral temperature.....	29
6.4.1	General.....	29
6.4.2	Scuffing integral temperature, $\vartheta_{\text{ints}}$ .....	29
6.4.3	Relative welding factor, $X_{\text{WrelT}}$ .....	34
<b>Annex A (informative) Examples .....</b>		<b>35</b>
<b>Annex B (informative) Contact-time-dependent scuffing temperature .....</b>		<b>44</b>
<b>Bibliography .....</b>		<b>49</b>