

DIN EN 17038-2:2022-08 (E)

Pumps - Methods of qualification and verification of the Energy Efficiency Index for rotodynamic pump units - Part 2: Testing and calculation of Energy Efficiency Index (EEI) of single pump units (includes Corrigendum :2021)

Contents		Page
European foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	Reference flow-time profiles and reference pressure control curves	8
4.1	General	8
4.2	Reference flow-time profiles	9
4.3	Reference pressure control curves	10
5	Determination of average electric power input P_{1,avg} by test	10
5.1	General	10
5.1.1	Test requirements	10
5.1.2	Test conditions	10
5.1.3	Measuring instrumentation	11
5.2	Calculation of load points	12
5.2.1	General	12
5.2.2	Determination of Q ₁₀₀ % and H ₁₀₀ %	12
5.2.3	~Determination of part load and over load points and reference control curve TM	13
5.3	Calculation of P _{1,avg}	14
5.3.1	General	14
5.3.2	Pump units evaluated with the reference flow-time profile for constant flow operation	14
5.3.3	Pump units evaluated with the reference flow-time profile for variable flow operation	14
5.3.4	Procedures for testing and evaluation of pump units with special pump types	15
6	Determination of the Energy Efficiency Index of pump units by the means of a semi-analytical model	16
6.1	General	16
6.2	The semi analytical model of the pump	17
6.3	Pump units in fixed speed operation	19
6.3.1	General	19
6.3.2	The model of the electric motor	20
6.3.3	Interaction of pump and motor	21
6.3.4	Determination of Q ₁₀₀ % from QBEP	22
6.3.5	Determination of the P _{1,avg,c} -value	23
6.4	Pump units with a Power Drive System (PDS)	24
6.4.1	General	24
6.4.2	The model of the Power Drive System (PDS)	26
6.4.3	Interaction between pump and PDS	29
6.4.4	Determination of Q ₁₀₀ % and H ₁₀₀ % from QBEP and HBEP	30
6.4.5	Determination of P _{1,avg,v} and P _{1,avg,c} for pump units with PDS	31
7	Determination of reference electric power input P_{1,ref}	32

8	Calculation of Energy Efficiency index (EEI)	35
	Annex A (normative) Scope	36
	Annex B (informative) Determination of additional supporting points for semi-analytical model based on empirical correlations	39
B.1	General	39
B.2	Additional supporting points for end-suction pumps (pump types ESOB, ESCC and ESCCi)	41
B.2.1	Additional supporting points at $Q/Q_{BEP} = 0,25$	41
B.2.2	Additional supporting points at $Q/Q_{BEP} = 0,1$	41
B.3	Additional supporting points for vertical multistage pump (MS-V)	42
B.3.1	Additional supporting points at $Q/Q_{BEP} = 0,25$	42
B.3.2	Additional supporting points at $Q/Q_{BEP} = 0,1$	42
B.4	Maximum model uncertainties	42
	Annex C (normative) Synthesis of the PDS supporting points from separate data for motor and CDM	46
C.1	General	46
C.2	Determination of the losses PL,CDM at the 3-supporting points needed for the PDS model	49
C.3	Determination of the losses PL,PDS at the 3 supporting points needed for the PDS model	50
	Annex D (informative) Uncertainties and tolerances of EEI-values	52
D.1	General remarks	52
D.2	The measurement uncertainty of the EEI-value determined by test	52
D.3	The uncertainty of the EEI-value determined by the application of models	55
D.3.1	General	55
D.3.2	Operation mode: Fixed speed	55
D.3.3	Operation mode: Variable speed	56
D.4	The total tolerance of the mean EEI-value	58
D.4.1	Determination of the mean EEI-value by testing only one pump unit	58
D.4.2	Determination of the mean EEI-value by testing a sample of M pump units of the same type series	60
D.4.3	Determination of the mean EEI-value by application of the semi-analytical model	60
	Annex E (informative) Mathematical solution of polynomial formulae of 3rd degree	63
	Annex F (normative) CDM model fall back values for Semi Analytical Model	65
	Bibliography	66