

DIN EN 16842-7:2019-06 (E)

Powered industrial trucks - Visibility - Test methods and verification - Part 7: Variable-reach and masted container trucks handling freight containers of 6 m (20 ft) length and longer

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 3 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Truck configuration | 7 |
| 4.1 | General | 7 |
| 4.2 | Position of container attachment | 7 |
| 4.3 | Tilt of mast (only applicable for masted trucks) | 7 |
| 4.4 | Position of cab | 7 |
| 5 | Test equipment | 7 |
| 6 | Test procedures for direct visibility | 7 |
| 6.1 | Lighting equipment position | 7 |
| 6.2 | Test paths for trucks handling containers | 8 |
| 6.3 | Measurement procedure | 11 |
| 6.4 | Test procedure for indirect visibility | 11 |
| 7 | Acceptance criteria | 11 |
| 7.1 | General | 11 |
| 7.2 | Direct visibility | 11 |
| 7.2.1 | General | 11 |
| 7.2.2 | Travelling visibility | 11 |
| 7.2.3 | Manoeuvring visibility | 11 |
| 7.3 | Indirect visibility | 11 |
| 7.4 | Criteria for container handling trucks | 12 |
| 8 | Test report | 13 |
| 9 | Information for use | 13 |