

DIN EN 16842-3:2019-06 (E)

Powered industrial trucks - Visibility - Test methods and verification - Part 3: Reach trucks up to and including 10000 kg capacity

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Truck configuration | 6 |
| 4.1 | General | 6 |
| 4.2 | Fork arm dimensions | 6 |
| 5 | Test equipment | 6 |
| 6 | Test procedures for direct visibility | 6 |
| 6.1 | Lighting equipment position | 6 |
| 6.1.1 | General | 6 |
| 6.1.2 | Stand-on operated trucks | 6 |
| 6.1.3 | Sit-on operated trucks | 8 |
| 6.2 | Test paths for reach trucks 10 000 kg | 8 |
| 6.3 | Measurement procedure | 10 |
| 6.4 | Test procedure for indirect visibility | 10 |
| 7 | Acceptance criteria | 10 |
| 7.1 | General | 10 |
| 7.2 | Direct visibility | 10 |
| 7.2.1 | General | 10 |
| 7.2.2 | Travelling visibility | 10 |
| 7.2.3 | Manoeuvring visibility | 10 |
| 7.2.4 | Fork arms | 10 |
| 7.3 | Indirect visibility | 10 |
| 7.4 | Criteria for reach trucks up to and including 10 000 kg rated capacity | 11 |
| 8 | Test report | 12 |
| 9 | Information for use | 12 |