

# ISO/TR 6336-31:2018-09 (E)

## Calculation of load capacity of spur and helical gears - Part 31: Calculation examples of micropitting load capacity

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Symbols and units .....</b>	<b>1</b>
<b>5</b>	<b>Example calculation .....</b>	<b>4</b>
<b>5.1</b>	<b>General .....</b>	<b>4</b>
<b>5.2</b>	<b>Example 1 Spur gear .....</b>	<b>5</b>
<b>5.2.1</b>	<b>General .....</b>	<b>5</b>
<b>5.2.2</b>	<b>Input data .....</b>	<b>5</b>
<b>5.2.3</b>	<b>Calculation according to method B .....</b>	<b>6</b>
<b>5.2.4</b>	<b>Calculation according to method A .....</b>	<b>13</b>
<b>5.2.5</b>	<b>Calculation of the permissible lubricant film thickness .....</b>	<b>14</b>
<b>5.3</b>	<b>Example 2 Spur gear .....</b>	<b>19</b>
<b>5.3.1</b>	<b>General .....</b>	<b>19</b>
<b>5.3.2</b>	<b>Input data .....</b>	<b>20</b>
<b>5.3.3</b>	<b>Calculation according to method B .....</b>	<b>21</b>
<b>5.4</b>	<b>Example 3 Helical gear .....</b>	<b>28</b>
<b>5.4.1</b>	<b>General .....</b>	<b>28</b>
<b>5.4.2</b>	<b>Input data .....</b>	<b>29</b>
<b>5.4.3</b>	<b>Calculation according to method B .....</b>	<b>30</b>
<b>5.4.4</b>	<b>Calculation according to method A .....</b>	<b>37</b>
<b>5.5</b>	<b>Example 4 Speed increaser .....</b>	<b>38</b>
<b>5.5.1</b>	<b>General .....</b>	<b>38</b>
<b>5.5.2</b>	<b>Input data .....</b>	<b>39</b>
<b>5.5.3</b>	<b>Calculation according to method B .....</b>	<b>41</b>
<b>5.5.4</b>	<b>Calculation according to method A .....</b>	<b>47</b>
Bibliography .....		49